

TOWNSHIP 23 RANGE 05 POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 6 and 7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 6 Page(s) 2381)

-----  
Set ¼ sec. post, from which  
A Fir 44" dia., bears S.54 ¾°W., 21 lks.  
A Fir 18" dia., bears N.3¾°E., 155 lks.

O.F. Thiel in 1933 found old cedar post in place and old trees standing. C.S. File 61/5

Oscar F. Thiel - For: Art Reckord - June 7, 1951 - Thiel's Book 20 Page 22 and C.S. File 61/5-12

-----  
Drove an iron rod 1" x 27" long for corner.  
Old SW tree standing, 60".  
Marked new trees;  
10" W.Fir S.45°E., 25.0 ft.  
9" W.Fir N.16°E., 67 ft.

Survey by Charles C. Hayden - For: Reese Lumber - Sept. 1952 - C.S. File 41/65

-----  
Found - ¾" Iron pipe, 3 x 3 post S6 ¼S.  
Hemlock 12" S.40°E., 25.9 ft. mkd. RS ¼ S BT.  
Fir 10" N.21°E., 67.1 ft. ¼ S BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey; Clete Putnam - Jan. 5, 1960 - C.S. File 49/42-38

-----  
Found - Orig. 44" now 66" Fir stump S.54 ¾°W., 13.9 ft. I open and find good scribing "BT".  
Also find 40" stump that may be orig. NE BT.  
I find geared axle at corner and 3" x 3" stake.  
Set Brass cap at cor. mkd: County Surveyors Office  
T 23 S R 5 W  
¼  $\frac{S}{S} \frac{6}{7}$   
1960

New BTs -13" W.Fir bears N.88°W., 18.3 ft. scribed ¼ S6 CSBT  
14" W.Fir bears S.45°E., 25.9 ft. shows good scars, I do not open. This BT recorded by Hayden as 12" Hemlock S.40°E., 25.9 ft.  
I also find Hayden's 10" Fir, N.21°E., 67.1 ft., should be N.17°E., 67.1 ft.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 6 & 7

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Douglas Co. Surveyors Office - Gary L. Langlitz, Deputy -  
F.C. Silagy, crew - March 28, 1978 - C.S. File 59/46-81

-----  
Found - Rotten remains of a scribed wood post, approx. 3" x  
3" (source unknown, probably Thiel)  
A 1" axle with gear, flush in ground, source  
unknown.  
3/4" I.P. found by Hayden in 1952 not found.  
A 1" I.P. extending 12" above ground with brass cap  
attached properly marked.  
An orig. 44" Fir now a 66" stump with scribing "BT"  
visible on previously opened blaze bears S.54  
3/4°W., 13.9 ft.  
Orig. NE BT an 18" Fir not found.  
A 22" G.Fir alive with well healed double blaze  
bears S.45°E., 25.9 ft. (Rec. 12" Hemlock  
S.40°E., 25.9 ft.)  
A 10" now 17" D.Fir alive with well healed double  
blaze bears N.17°E., 67.1 ft. (Rec. N.21°E., 67.1  
ft.)  
A 13" W.Fir now an 18" snag, with well healed blazes  
bears N.88°W., 18.3 ft.  
Condition report only, no new monuments or accessories set.

Fd. OK, Dec. 1993, Daniel Baker, M 118-43

Fd. & used on BLM dependent resurvey by Wayne Rogers & Bryan  
Seibold, Cadastral Surveyors, under Group #1832 surveyed July  
- Oct. 1997 - (DCSO recs. Vol. 53 Pg(s) 20285)

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike  
- 1/25/2006 - C.S. File 67/14-3

-----  
Found - 2½ BC (properly mkd) on 1¼" dia., iron pipe firmly  
set projecting 12" above ground with flanged axle  
flush w/ground on east edge.  
Orig. 44" dia., Fir now 60" dia., x 5 ft. tall  
rotting stump scribe marks "1/4 S BT" visible on  
opened exposed blaze, bears S.50°W., 16.7 ft.  
(rec. S.54¾°W., 13.9 ft.)  
10" now 30" dia., W.Fir fully healed double blaze  
visible bears S.45°E., 26.6 ft. (rec. S.45°E.,  
25.0 ft.) 1951 BT  
10" now 19" dia., x 4 ft. tall D.Fir stump fully  
healed double blaze visible, bears N.17°E., 67.1  
ft. (agrees w/DCSO 1978 rec.) 1951 BT  
No evidence fd of 1978 NW BT (rec. N.88°W., 18.3 ft)  
continued next page

TOWNSHIP 23 RANGE 05 POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 6 and 7

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

New -	13" D.Fir, double blazed & scribed "¼ S7 CS BT" bears S.51°W., 30.0 ft. 26" dia., x 2½" tall W.Fir stump w/PK nail driven over center of root crown bears N.19½°W., 47.6 ft
Note -	Corner lies on nearly level bench with timber to the south & young re-growth north. Compass decl. 16½°E.