

TOWNSHIP 23 RANGE 05 POINT IDENTIFIER # 200100

PRIMARY CORNER DESCRIPTION Sec Cor for 31 & 32; 5 & 6 of T24-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original -Robert Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records Vol. 6 Page(s) 2346)

Set Post, cor. to secs. 31, 32, 5 and 6, from which
A Y.Oak 36" dia., bears N.57°W., 393 lks.
A Y.Oak 16" dia., bears S.60½°W., 270 lks.
A Y.Oak 18" dia., bears S.82°E., 107 lks.
A Y.Oak 24" dia., bears N.88 3/4°E., 196 lks.

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey and Clete Putnam - Dec. 14, 1959 - C.S. File 49/42-31

Found - B.Oak snag, now 48", N.57°W., 259.4 ft., found faint traces of scribing in rotten wood.
Remnants of rotted Oak stump, N.88 3/4°E., 129.4 ft., found portion of wood with good reverse scribing "BT"
Oak tree, dead and down, S.82°E., 70.6 ft., no scribing found.
Stump hole and portion of burned Oak log, S.60½°W., 178.2 ft., no scribing found, too badly burned.

At corner, Set Iron pipe with brass cap marked:

County Surveyors Office

S 31 | S 32 T23S R5W
S 6 | S 5 T24S R5W

1959

Blaze and scribe following trees:

8" W.Oak S.63½°E., 45.1 ft. mkd. T24S R5W S5 CS BT.
10" B.Oak S.87°W., 93.5 ft. mkd. T24S R5W S6 CS BT.
15" D.Fir N.53½°W., 23.4 ft. mkd. T23S R5W S31 CS BT
11" D.Fir N.48°E., 17.6 ft. mkd. T23S R5W S32 CS BT.

1½" sq. Iron bar bears S.47°W., 1.8 ft.

Fence corner, 2 ft. N.W.

Fd. July 1990, Land partition, 1990-0035

Fd. OK, March 1991, M 111-64

Fd. OK, July 1993, M 117-52

Found OK by H. Pieske, Nov. 2000 - M132-58

Fd. ok by Douglas Co. Surveyors Office - Stephen J. Flause - John Pike - 8/2/2007 - C.S. File 67/24-4

Fd. BC 4/2013 by Todd Patterson, M165-18