

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 29 and 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 6 Page(s) 2374)

-----  
Set ¼ sec. post, from which  
A Y.Oak 16" dia., bears N.58°W., 60 lks.  
A Fir 28" dia., bears N.7°E., 75 lks.

Survey by Douglas Rosecans - For: Florence Cogswell - July 1978 - M 72-17

-----  
Found - Stone on fence line, 4" x 4", 6" above ground, ¼ scribed on W. face.

Douglas County Surveyors Office - Gary L. Langlitz, Karen Reed, crew - March 6 and 22, 1979 - C.S. File 60/24-15

-----  
CORNER REPORT ONLY  
Found - A rock, 4" x 7" x 18", 6" above ground. Only markings visible are "1\1 ( L" ) A rock monument has never been recorded for this corner.  
A 22" Fir stump bears S.14°W., 35.5 ft., visible scribing "BT" on well rotted stump, partial scribing visible on remains of Fir alongside stump. (No record this BT)  
No evidence of record BTs from rock position. (Scribing on Fir stump faces approx. position of rock)  
Reversed record measurements from Fir stump (using record orig. Fir BT) find nothing to indicated corner. Using position where measurements fell, search for orig. Oak BT, nothing found. Reversing Oak brgs. & Dist., nothing found.

Survey by Russell Pinard, L.S. #958 - For: Woolley Lumber - March 1979 - M 76-48

-----  
Found stone per M 72-17  
Set - 1" Iron pipe with brass cap mkd: T23S R5W ¼ S30 S29 RLS #958 1979".  
BTs - 12" Madrone scribed "¼ S29 BT" bears N.75°E., 57.0 ft.  
6" Madrone scribed "¼ S30 BT" bears N.16°30'W., 53.4 ft

continued next page

TOWNSHIP 23 RANGE 05 POINT IDENTIFIER # 200240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 29 and 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Ken Hoffine - For: Lone Rock Timber Co. - Nov. 2000 - M136-28  
-----

Found - 1979 brass cap in good condition mkd: ¼ S29 S30 RLS  
958 1979

18" D.Fir bears S.48°W., 19.1 ft. LRT location tag  
& healed face, NO REC.

Corner lies in fence corner on west edge of power  
line R/W. Fence runs North, South, & East.

DCSO-GIS Corner visitation - 5/2/2007 - Typed: 1/20/2011 -  
C.S. File 67/33-1  
-----

Monument - 2½" BC/IP