

TOWNSHIP 23 RANGE 05 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Sec Cor for 19, 20, 29 and 30

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 6 Page(s) 2374)

-----  
Set post, cor. to secs. 19, 20, 29 and 30, from which  
A W.Oak 15" dia., bears N.6¼°E., 335 lks.  
A W.Oak 18" dia., bears S.57¼°E., 650 lks.  
Made trench, no other trees being near.

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey; Clete Putnam - Nov. 1959 - C.S. File 49/42-21

-----  
Found - Orig. 18" now 30" W.Oak S.56¼°E., 429.0 ft.  
Remains of Oak tree checks record bearing from cor.  
I find dist. to be 191.0 ft. (Rec. 221.1 ft. No scribing found.)

Find 13"x9"x4" stone with cross on top at corner.  
Set Brass cap alongside stone mkd: County Surveyors Office

T 23 S R 5 W  
S 19 | S 20  
S 30 | S 29  
1959

New BTs -18" R.Fir bears S.85°E., 64.6 ft. scribed S29 T23S  
R5W CS BT.  
20" W.Oak bears N.80°E., 83.6 ft. scribed S20 T23S  
R5W CS BT.  
8" W.Oak bears N.60°W., 140.0 ft. scribed S19 T23S  
R5W CS BT.

No trees near to SW.  
Cor. is at fence corner, fences running North and East

Fd. OK, July 1981, Bruce Shaner, M 90-1

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 8/28/2000 - C.S. File 66/16-37

-----  
Found - 1959 36" long brass cap/iron pipe out of ground leaning against a 2 way fence corner. Fence line runs North & East.

West side of fence corner eroded away, found 13"x9"x4" stone marked with a "+" on top and "30" on one side. Approx. 10 ft. SW of fence corner in eroded ditch. (Source unknown)

18" now 25" dia., D.Fir with a fully healed double blaze bears S.85°E., 64.6 ft. (1959)

8" now 15" dia., W.Oak with a fully healed double blaze, bears N.60°W., 140.0 ft. (1959)

continued next page

PRIMARY CORNER DESCRIPTION Sec Cor for 19, 20, 29 and 30

Alias	Description
Alias	Description
Alias	Description
Alias	Description

20" now 27" dia., multi trunked W.Oak with a fully healed double blaze on 13" dia. West trunk, root crown bears N.80°E., 83.6 ft. 1959  
18" now 32" dia., W.Oak showing evidence of being previously opened, bears S.57¼°E. 429.0 ft. (OBT)  
Set - A 5/8" by 5 ft. long iron rod with DCS0 alum. cap, protrudes 4" above ground, 1.5 ft. West of fence corner at calculated corner position, marked:  
DOUGLAS CO.  
19|20  
30|29  
2000  
SURVEYOR  
Reset - 1959 DCS0 BC/IP N.45°E., 20.0 ft., from corner, add marks "S45W 20 FT TO COR RESET 2000", protrudes 5" above ground.  
Set stone along south edge of BC/IP protrudes 1" above ground  
Note - BC/IP and stone now references to I.R. at corner.  
"+" on stone 0.4 ft. south of BC/IP

Fd. Ok by Ken Hoffine, 1/2006 - M149-61

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2315, Surveyed May/June 2010 - DCS0 records Vol. 57 Page(s) 22767-8  
-----  
The cor. of secs. 19, 20, 29, and 30, perpetuated by Byron, in 1959, perpetuated by Smith, in 2000, monumented with an iron rod, 5/8" dia., firmly set, flush with the ground, with aluminum cap (properly) mkd.  
from which the remaining original bearing tree  
An oak, 29" dia., bears S.57¼°E., 432.1 ft. with a healed double blaze. (Record, 429.0 ft.)  
and bearing trees mkd. by Byron  
An oak, 26" dia., bears N.80¾°E., 85.3 ft., with a healed double blaze.  
A fir, 27" dia., bears S.84¾°E., 66.5 ft., with a healed double blaze.  
An oak, 16" dia., bears N.60°W., 138.2 ft., with a healed double blaze.  
and an accessory established by Smith  
An iron post, 1½" dia., firmly set, projecting 6" above the ground, bears N.49°36'47"E, 20.94 ft., with brass cap mkd. RESET T23S R5W S19 S20 S29 S30 S45W 20FT TO COR 1959, alongside of which is a stone, 9x9", firmly set, projecting 1" above the ground, with cross on top.  
continued next page

TOWNSHIP 23 RANGE 05 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19, 20, 29 and 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

From this cor., the cor. of woven wire fences extending N.  
and E. bears N.6¼°E., 3.3 ft. dist.  
(NAD 1983 (CORS))  
Latitude: 43°32'53.75"N.      Longitude: 123°19'36.22"W.