

TOWNSHIP 23 RANGE 05 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 17, 18, 19 and 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 6 Page(s) 2376)

-----  
Set post, cor. to secs. 17, 18, 19 and 20, from which  
A Fir 40" dia., bears N.14°W., 11 lks.  
A Fir 12" dia., bears N.66½°E., 84 lks.  
A Fir 18" dia., bears S.84°E., 36 lks.  
A Fir 16" dia., bears S.65°W., 100 lks.

Survey by Wilford Haines - For: Western Land & Timber Co. - Feb. 1959 - M 14-8

-----  
Found - 40" Fir N.14°W., 11 lks. (dead)  
16" Fir S.65°W., 100 lks. (gone)  
12" Fir N.66½°E., 84 lks. (down)  
18" Fir S.84°E., 36 lks.  
Set 1" x 1" x 36" T Iron with brass cap inscribed "Survey Point Wilford N. Haines #239"

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey; Clete Putnam - Nov. 1959 - C.S. File 49/42-19

-----  
Found - Orig. 40" now 50" Fir N.14°W., 7.3 ft. shows scribing "S" on old face.  
Orig. 18" now 32" Fir S.84°E., 23.8 ft., shows old scars. I do not open.  
Stump holes that check bearings and distance for orig. SW and NE BTs.  
Also find Haines' angle iron and cap at corner.  
New BTs -8" W.Fir bears N.39½°E., 13.9 ft. scribed S17 T23S R5W CS BT.  
40" R.Fir bears S.84°W., 34.4 ft. scribed S19 T23S R5W CS BT.

Fd. OK, Dec. 1989, C.S. File 63/104-47

Fd. OK, April 1991, M 111-76

Survey by Ken Hoffine - For: Lone Rock Timber - Sept. 1993 - M 117-72

-----  
Found - Haines T-Iron with brass washer on top in good condition.  
23" W.Fir bears N.39½°E., 13.9 ft., well healed face and BT tag.  
(Cont. Next Page)

TOWNSHIP 23 RANGE 05 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 17, 18, 19 and 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

50" D.Fir snag bears N.14°W., 7.3 ft. scribing visible and BT tag.  
56" D.Fir bears S.84°W., 34.4 ft. well healed face and BT tag.  
17" D.Fir bears S.34°W., 26.5 ft. I blaze and tag tree.  
Corner lies on a North facing slope approx. 150 ft. South of small ridge.

Survey by Daniel Baker - For: Weyerhaeuser Co. - March 15, 1994 - M 118-60  
-----  
Found - Haines T bar and disk.  
23" W.Fir N.38½°E., 14.4 ft. closed face.  
23" Fir S.34½°E., 26.5 ft. Lone Rock tag, (Rec. S.34°W.)  
52" Fir S.82½°W., 34.4 ft. closed face, BLM tag.  
57" Fir N.21 3/4°W., 7.8 ft., visible scribe BLM tag

Found OK by D. Edwards, Jan. 2003 - M141-60

DCS0-GIS Corner visitation - 2/6/2006 - Typed: 1/20/2011 - C.S. File 67/33-1  
-----  
Monument - T-iron  
Comment - OK; 3 live BTs, 1 BT stump.

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2315, Surveyed May/June 2010 - DCS0 records Vol. 57 Page(s) 22771-2  
-----  
The cor. of secs. 17, 18, 19, and 20, perpetuated by Haines in 1959, perpetuated by Byron, in 1959, perpetuated by Hoffine, in 1993, perpetuated by Baker, in 1994, monumented with a T-shaped iron rod, 3/4" dia., firmly set, projecting 4" above the ground, with 1" dia. brass disk affixed to top, mkd. WILFORD N HAINES 239 SURVEY POINT DRAIN ORE, from which the remains of an original bearing tree  
A decayed fir stump, size indeterminate, bears N.14°W., 7.3 ft., with scribe marks R W T23S S18 visible on an open blaze.  
and bearing trees mkd. by Byron  
A fir, 28" dia., bears N.37°E. 14.0 ft. with a healed blaze.  
A fir, 58" dia., bears S.84¼°W., 35.0 ft., with a healed blaze.  
and a bearing tree mkd. by Hoffine

continued next page

TOWNSHIP 23 RANGE 05 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 17, 18, 19 and 20

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

A fir, 26" dia., bears S.35°E., 26.2 ft., with a healed blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 18" in the ground, with brass cap mkd

T23S R5W  
S 18 | S 17  
S 19 | S 20  
2010

from which a new bearing tree

A fir, 6" dia., bears N.71½°W, 10.8 ft., mkd. X BT.

Deposit a magnet in a white plastic case at the base and the T-shaped iron rod, bent in half, 36" long, alongside the stainless steel post.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2961, surveyed Oct. 2019/Jan. 2020- (DCSO records Vol. 59 Pages 24033-5 & BLM Plat 2022-1 T23-5)

-----  
The cor. of secs. 17, 18, 19, and 20, reported by Skeesick in 2010, monumented with a stainless steel post, 2½" dia., firmly set, projecting 14" above ground, with a brass cap (properly) mkd.

from which the remains of the BTs reported by Skeesick

A fir, 30" dia., bears N.37°E., 14.0 ft. with a healed blaze.

A fir, 26" dia., bears S.35°E., 26.2 ft., with axe marks visible on bark.

A fir snag, 56" dia., bears S.84¼°W., 35.0 ft., with a healed blaze.

A fir, 6" dia., bears N.71½°W., 10.8 ft., with scribe marks X BT visible on partially healed double blaze.

A decayed fir snag, size indeterminate, bears N.14°W., 7.3 ft., with scribe marks T23S S visible on open blaze.

(Original)

and a new bearing tree

A fir, 25" dia., bears S.63½°W., 19.5 ft., mkd. T23S R5W S19 BT on bark.

From the corner

E., 105 ft., spur, slopes N.20°E.

N., 115 ft., draw, drains N.25°E.

A search was made for the original line tree on the north half of the south half of the section line between sections 17 and 18, and none were recovered.