

TOWNSHIP 23 RANGE 05 POINT IDENTIFIER # 240300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 29

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Robert Elder and Henry Gile, Deputy Surveyors,  
under Contract #31 dated April 7, 1853 (DCSO records Vol. 6  
Page(s) 2375)

-----  
Set ¼ sec. post, from which  
A Y.Oak 16" dia., bears N.47½°W., 106 lks.  
A Y.Oak 16" dia., bears S.56½°W., 159 lks.

Vol. 2 Page 264 - Date ? - By ?

-----  
Set Cedar post 4x4x3 ft. from which  
R.Fir 12" bears N.16°12'E., 39 lks.  
R.Fir 18" bears S.23°14'W., 73 lks.  
(Old BTs in evidence)

Douglas Co. Surveyors Office - James Byron, Deputy - Crew,  
Milo Godfrey; Clete Putnam - Dec. 14-18, 1959 - C.S. File  
49/42-34

-----  
Found - Fir stump, now 36" dia., S.23¼°W., 48.2 ft. Cut open  
and found good scribing "B"  
Fir stump, now 24", N.16°E., 25.7 ft., showing good  
scar, did not open.

Set Brass cap at cor. mkd: County Surveyors Office  
T 23 S R 5 W  
¼  $\frac{S\ 20}{S\ 29}$   
1959

Blaze and scribe 2 new trees:  
6" D.Fir N.44½°E., "¼ S20 CS BT", 12.6 ft.  
4½" D.Fir S.44½°E., "¼ S29 CS BT", 17.6 ft.

Fd. OK by K. Hoffine, Nov. 2000 - M136-28