

TOWNSHIP 23 RANGE 05 POINT IDENTIFIER # 240400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 6 Page(s) 2377)

Set ¼ sec. post, from which
A Fir 18" dia., bears N.20°E., 104 lks.
A W.Oak 11" dia., bears S.24°W., 211 lks.

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey; Clete Putnam - Nov. 1959 - C.S. File 49/42-18

Found - Orig. 18" now 36" Fir, stump, N.20°E., 68.6 ft. I open and find good scribing.
Orig. 11" now 24" W.Oak S.24°W., 139.3 ft. I fall tree and look for scribing, none found, center rotted.

Set Brass cap at cor. mkd: County Surveyors Office
T 23 S R 5 W
¼ $\frac{S\ 17}{S\ 20}$
1959

New BTs -15" R.Fir bears S.51½°W., 45.0 ft. scribed ¼ S20 CS BT.
26" R.Fir bears N.2°W., 98.4 ft. scribed ¼ S17 CSBT

Found OK by D. Edwards, Jan. 2003 - M141-60
Fd. Ok N. Hibbs, 12/2006 - 2007-0159 A-C

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2961, surveyed Oct. 2019/Jan. 2020- (DCSO records Vol. 59 Pages 24033-5 & BLM Plat 2022-1 T23-5)

The ¼ sec. cor. of secs. 17 and 20, perpetuated by Byron, in 1959; subsequently perpetuated by person(s) unknown; monumented with an iron post, 1¼" dia., firmly set, projecting 8" above ground, with a brass cap (properly) mkd. from which the remains of an original bearing tree
A decayed fir stump, 30" dia., bears N.20°E., 68.6 ft., with scribe marks ¼ BT visible on open blaze.
and the remains of the bearing trees mkd. by Byron
A decayed fir stump, 22" dia., bears S.52°W., 45.0 ft., with a healed double blaze.
A broken, decayed fir stump, 24" dia., bears N.2°W., 97.7 ft., alongside of which is a down decayed fir trunk, no marks visible.

and the remains of a bearing tree mkd. by person(s) unknown

continued next page

TOWNSHIP 23 RANGE 05 POINT IDENTIFIER # 240400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir stump, 16" dia., bears N.1°E., 25.8 ft., with a healed blaze.
and new bearing trees
A fir, 6" dia., bears S.18¼°W., 23.5 ft., mkd. ¼ S20 BT.
A fir, 11" dia., bears N.6°W., 24.9 ft., mkd. ¼ S17 BT.
From the corner
W., 105 ft., spur, slopes S.10°E.
NAD 1983 (2011)
Lat: 43°33'45.78"N Long: 123°19'00.23W