

TOWNSHIP 23 RANGE 05 POINT IDENTIFIER # 240600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 6 Page(s) 2380)

Set ¼ sec. post, from which
A Y.Oak 16" dia., bears S.55 ¾°W., 100 lks.
A Fir 18" dia., bears N.38 ¾°W., 136 lks.

O.F. Thiel and Peterson - June 29, 1900 - Vol. 2 Page 262

Set a B.Oak post, from which
A Fir 16" dia., bears N.67½°W., 40 lks. dist.
A Fir 20" dia., bears S.36°E., 50 lks. dist.
The SW BT, is dead and very badly decayed but the orig. marks are plain by cutting.
The NW tree has been down year ago and stump badly decayed

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey; Clete Putnam - Jan. 5, 1960 - C.S. File 49/42-37

Found - 16" now 30" Fir, down. I open and find good scribing "S1".
No trace of orig. BTs found nor Theil's SE BT.
12" x 6" x 4" rock at corner chiseled ¼S on North and South faces.

Set Brass cap alongside corner stone marked:
County Surveyors Office
T 23 S R 5 W
¼ $\frac{S\ 5}{S\ 8}$
1960

New BTs -8" double B.Oak bears N.85°W., 26.3 ft. scribed ¼ S5 CS BT.
10" B.Oak bears N.11°W., 26.5 ft. scribed ¼ S5 CSBT.

Fd. OK, Oct. 1969, DCSO, V. Tracy, C.S. File 54/16-59A

BLM resurvey by James E. Jelley and Wayne L. Rogers, under Group #1119, surveyed 1982 (DCSO records Vol. 46 Page 17671)

The ¼ sec. cor., perpetuated and recorded by Thiel in 1900 from original evidence no longer in existence, and further perpetuated and recorded by Byron in 1960, monumented with an iron post 1¼" dia., firmly set, projecting 10" above ground with 1960 brass cap.
from which bearing trees mkd. by Byron
(Cont. Next Page)

TOWNSHIP 23 RANGE 05 POINT IDENTIFIER # 240600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

An Oak 18" dia., bears N.87½°W., 39½ lks. dist., with
healed double blaze.
A W.Oak 20" dia., bears N.10½°W., 39½ lks. dist., with
healed double blaze.
and a new bearing tree
A Fir 12" dia., bears S.54¼°E., 187 lks. dist. mkd. ¼ S8BT