

TOWNSHIP 23 RANGE 05 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 8, 9, 16 and 17

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 6 Page(s) 2370)

-----  
Set post, cor. to secs. 8, 9, 16 and 17, from which  
A Y.Oak 22" dia., bears N.46¼°W., 322 lks.  
A Y.Oak 24" dia., bears S.46½°E., 423 lks.  
A Y.Oak 20" dia., bears S.82½°W., 351 lks.  
A W.Oak 18" dia., bears N.31½°E., 153 lks.

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey; Clete Putnam - Nov. 3, 1959 - C.S. File 49/42-20

-----  
Found - Orig. 22" now 36" B.Oak N.46¼°W., 212.5 ft., shows good scar. I do not open.  
Orig. 24" now 36" Y.Oak S.46½°E. I find should be S.44½°E., 279.2 ft. I open and find good scribing "16"  
Orig. 18" now 36" W.Oak N.31½°E., 101.0 ft. shows good scars I do not open.

Set Brass cap at cor. mkd: County Surveyors Office  
T 23 S R 5 W  
S 8 | S 9  
S 17 | S 16  
1959

New BTs -12" R.Fir bears S.31½°E., 60.0 ft. scribed S16 T23S R5W CS BT.  
12" R.Fir bears S.56½°W., 103.8 ft. scribed S17 T23S R5W CS BT.  
6" W.Oak bears N.7°W., 72.0 ft. scribed S8 T23S R5W CS BT.  
36" W.Oak (Orig.) N.31½°E., 101.0 ft. scribed S9 T23S R5W CS BT.  
Sec. Cor. at 3-way fence corner, fences running E., W. and S.

Fd. Ok N. Hibbs, 12/2006 - 2007-0159 A-C