

PRIMARY CORNER DESCRIPTION No. 1/4 for Section 4 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 6 Page(s) 2337)

Set ¼ sec. post in bed of small stream , from which
 A Y.Oak 8" dia., bears S.88½°W., 50 lks.
 A Maple 16" dia., bears S.6½°E., 25 lks.

Wilford N. Haines - For: Woolley Logging Co. - August 1967 H En. 3 and F.B. H-110 (this information not filed until Sept. 1990)

Found - Stone cairn buried 2.0 ft. West of stream.
 Set 5/8" Steel rod 1 ft. West of stones. Scribed:
 6" Fir S.35°W., 33.9 ft.
 8" Fir S.69°E., 30.1 ft.

BLM resurvey by James E. Jelley and Wayne L. Rogers, under Group #1119, surveyed 1982 (DCSO records Vol. 46 Page(s) 17665-66)

The standard ¼ sec. cor. of sec. 4, at proportionate distance, based on the 1855 Gordon and Gardner resurvey; there is no remaining evidence of the original corner.
 Set an aluminum post 28" long, 2½" dia., 24" in the ground, with alum. cap mkd:

1/4 S 4
T 23 S R 5 W
SC
1983

from which
 A Fir 8" dia., bears S.34 3/4°E., 105 lks. dist., mkd. ¼ S4 SC BT.
 A Cedar 10" dia., bears S.80°W., 88 lks. dist., mkd. ¼ S4 SC BT.

From this same point, a locally established point, bears S.38°34'W., 0.271 chs. dist., monumented with an iron rod, 1/2" dia., firmly set, projecting 4" above ground, from which remains of bearing trees mkd. by person(s) unknown:

A Fir 12" dia., bears S.70 3/4°E., 47 lks. dist., with scribe marks ¼ S visible on partially healed double blaze.
 A Fir 11" dia., bears S.33½°W., 50 lks. dist., with scribe marks ¼ S4 visible on partially healed double blaze.

(Cont. Next Page)

TOWNSHIP 23 RANGE 05 POINT IDENTIFIER # 340700

PRIMARY CORNER DESCRIPTION No. 1/4 Corner for Section 4 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

An Oak snag, 17" dia., bears N.74 3/4°W., 22 lks. dist., with scribe marks ¼ S visible on opened blaze. (For information above re. "person(s) unknown", see Haines Field book #110 as filed with the DCSO)

Survey by Ken W. Hoffine - For Lone Rock Timber - Feb. 1994
M 118-66

Found - BLM Alum. cap .2 ft. above ground.
9" D.Fir, high stump, bears S.35°E., 69.5 ft. well healed scar and BLM tag.
10" Cedar bears S.80°W., 58.0 ft., destroyed by logging.
New BT - 11" Cedar bears S.30°W., 29.6 ft., I scribed SC ¼ S4 BT.
Corner lies on SW slope, a South flowing creek bears West 10 ft., an old fence line bears East, 10 ft.

Fd. OK, K. Hoffine - Nov. 1996 - M 126-21

DCSO-GIS Corner visitation - 12/13/2008 - Typed: 1/18/2011 -
C.S. File 67/33-1

Monument - 3" Alum. cap Comment - (needs) rehab