

TOWNSHIP 23 RANGE 05 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Witness Cor. Secs. 21, 22, 27, & 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____


Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 6 Page(s) 2362)

Set post, cor. to secs. 21, 22, 27, & 28 from which
 An Ash, 14" dia., bears S.61¼°W., 1123 lks.
 An Ash, 14" dia., bears S.56°E., 1279 lks.

BLM dependent resurvey by Wayne Rogers & Bryan Seibold, Cadastral Surveyors, under Group #1832 surveyed July - Oct. 1997 - (DCSO recs. Vol. 53 Pg(s) 20270 & 20273-4)

Page 20270
 The true point for the cor. of secs. 21, 22, 27 & 28, at proportionate distance, there is no remaining evidence of the original corner; point falls in the north-bound lane of Interstate 5, and is not monumented

Pages 20273-4
 Point selected for the witness cor. to the cor. of secs. 21, 22, 27 and 28.
 Set a stainless steel post, 28" long, 2½" diam., 24" in the ground, with brass cap mkd.



from which
 An ash, 32" diam., bears N.18°E., 262 lks., mkd. X BT.
 Deposit a magnet in a white plastic case at the base of the stainless steel post and set an orange carsonite post alongside.

The corner is located in a woven wire fence, extending N.15°E. and S.15°W. and W., 1.54 chs. from the concrete barriers between the north and south bound lanes of Interstate 5, asphalt-surfaced, 130 lks. wide, bears N.25°E. and S.25°W.

Fd. BC by ODOT, 9/2009 I5-025D
 Fd. BC 7/2018 - By D Edwards, M174-55