

TOWNSHIP 23 RANGE 05 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Sec Cor for 15, 16, 21 and 22

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 6 Page(s) 2363)

-----  
Set post, cor. to secs. 15, 16, 21 and 22, whence  
A Y.Oak 16" dia., bears N.15½°E., 111 lks.  
A W.Oak 16" dia., bears S.53°E., 244 lks.  
A W.Oak 15" dia., bears S.37½°W., 302 lks.  
A W.Oak 18" dia., bears N.82½°W., 179 lks.

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey; Clete Putnam - Jan. 19, 1960 - C.S. 49/42-48

-----  
Found - Orig. 18" now 24" Oak, down, N.82½°W., 118.1 ft. I open and find good reverse scribing "3 or BT". This BT was cut years ago and is now in ditch line. I do not find stump, believe it was in ditch at butt of tree.  
Oak stump hole that checks record bearing and distance for SW BT.  
3" x 3" sq. Oak stake, old, on ground at corner.  
No other orig. BTs found.

Set Brass cap at cor. mkd: County Surveyors Office

T 23 S R 5 W  
S16 | S15  
S21 | S22  
1960

New BTs -8" W.Oak bears N.52°W., 12.4 ft. scribed S16 T23S R5W CS BT.  
10" W.Oak bears N.45°E., 11.8 ft. scribed S15 T23S R5W CS BT.  
7" B.Oak bears S.5°W., 7.5 ft. scribed S21 T23S R5W CS BT.  
(?) R.Fir bears S.75°E., 74.4 ft. scribed S22 T23S R5W CS BT.

BLM dependent resurvey by Wayne Rogers & Bryan Seibold, Cadastral Surveyors, under Group #1832 surveyed July - Oct. 1997 - (DCSO recs. Vol. 53 Pg(s) 20273)

-----  
The cor. of secs. 15, 16, 21 & 22, perpetuated by Byron, in 1960, from original evidence no longer in existence, monumented with an iron post, 1½" diam., firmly set, projecting 14" above ground, with brass cap mkd.

continued next page

TOWNSHIP 23 RANGE 05 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

COUNTY SURVEYORS OFFICE

T 23 S R 5 W

S 16 | S 15

S 21 | S 22

1960

from which the remains of bearing trees mkd. by Byron

An oak, 18" diam., bears N.44½°E., 17½ lks., with healed blaze.

A fir, 31" diam., bears S.74 3/4°E., 113 lks., with healed blaze.

An oak, 14" diam., bears S.5¼°W., 11 lks., with healed blaze.

and a new bearing tree

The most easterly trunk of a double trunk oak, 6" diam., bears N.42°W., 32½ lks. mkd. T23S R5W S16 BT.

The corner is located in a large blackberry thicket and E., 0.75 chs. dist. of a seasonal creek, drains N.45°E.