

TOWNSHIP 23 RANGE 05 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 6 Page(s) 2364)

Set ¼ sec. post, from which
A Y.Oak 14" dia., bears N.61°E., 58 lks.
A Y.Oak 20" dia., bears S.37°W., 165 lks.

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey; Clete Putnam - Jan. 19, 1960 - C.S. 49/42-43

Found - Orig. 14" now 34" down Oak, N.61°E., 38.3 ft. I open and find good scribing "¼"
Orig. SW BT not found.
8" x 12" x 2" stone at corner.

Set Brass cap alongside corner stone mkd:
County Surveyors Office
T 23 S R 5 W
¼ S16 | S15
1960

New BTs -10" W.Oak bears S.32°W., 15.5 ft. scribed ¼ S16 CSBT
9" W.Oak bears N.45°E., 4.3 ft. scribed ¼ S15 CS BT.
N-S fence 3 ft. South of corner.

Fd. OK - by David Edwards - 06/18/97 - C.S. 65/12-11