

TOWNSHIP 23 RANGE 05 POINT IDENTIFIER # 440100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 34 & 3 T24-5

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records Vol. 6 Page(s) 2345)

-----  
Set ¼ sec. post, from which  
A Fir, 18" dia., bears N.88°W., 26 lks.  
A Laurel, 12" dia., bears S.34°W., 56 lks.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Deputy & crew - C.S. File 54/16-67A - 1969

-----  
Corner not found.  
Chopped into several old fir stumps - no OBTs found - cleared & burned also.

BLM dependent resurvey by Wayne Rogers & Bryan Seibold, Cadastral Surveyors, under Group #1832 surveyed July - Oct. 1997 - (DCSO recs. Vol. 53 Pg(s) 20271)

-----  
The ¼ sec. cor. of secs. 3 & 34, determined at record bearing and distance from the remains of an original bearing tree:  
A fir stump, 25" diam., bears N.88°W., 26 lks., with scribe marks BT visible on opened blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" diam., 25" in the ground, with brass cap mkd.

T 23 S R 5 W  
S 34

¼

S 3

T 24 S

1997

from which

A fir, 7" diam., bears N.22°E., 53 lks., mkd. ¼ S34 BT.

The most northerly trunk of a quadruple trunk maple, 11" diam., bears S.52°E., 54 lks., mkd. ¼ S3 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Wayne Rogers, i.e. Engineering - For: Duane Duncan - 2/2000 - M 134-23

-----  
Fd. brass cap as per 1997 BLM survey

Fd. OK 7/2018 - By D Edwards, M174-55

Fd. OK 12/2019 - By D Edwards, M176-40