

TOWNSHIP 23 RANGE 05 POINT IDENTIFIER # 500340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 22 and 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 6 Page(s) 2357)

Set ¼ sec. post, from which
A Y.Oak 30" dia., bears S.80°E., 80 lks.
A Y.Oak 26" dia., bears N.53½°W., 645 lks.

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey; Clete Putnam - Jan. 1960 - C.S. File 49/42-7

Found - Dead, rotten Oak snag, now 42", S.80°E., 52.8 ft. chopped open and found fragmentary scribing, unreadable but unmistakable.

B.Oak, alive and standing, N.53½°W., 427.7 ft. instead of 425.7 ft. Did not open this tree.

Set Brass cap at cor. mkd: County Surveyors Office

T 23 S R 5 W
¼ S22 | S23
1960

Blaze and scribe new BTs:

17" D.Fir S.83°E., 24.3 ft. mkd. ¼ S23 CS BT.

16" W.Oak S.40½°W., 56.6 ft. mkd. ¼ S22 CS BT.

Fd. OK, DCSO, R.Tracy, Oct. 1969, C.S. File 54/16-62A

FD. brass cap & 2 BTs by D. Edwards 9/2005 - M148-40

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike - 5/23/2007 - C.S. File 67/21-43

Found - 2½" dia., brass cap properly mkd. on 1¼" O.D. iron pipe, firmly set, projects 14" above ground.

16" now 27" dia., W.Oak, healed double blaze, bears S.40½°W., 56.6 ft., agrees w/rec. 1960 BT

17" now 28" dia., D.Fir, healed double blaze, bears S.83°E., 24.3 ft. agrees w/rec. 1960 BT.

New - 17" dia., W.Oak, double blazed & scribed "¼ S23 CS BT" bears N.69°E., 66.1 ft.

No trees within reasonable dist. to NW.

Note - Lies on mostly cleared gentle west facing slope. Compass decl. 16¼°E.

Fd. BC as per DCSO 2007 ren. 5/2013, Todd Catterson; M165-19

Fd. BC 7/2018 - By D Edwards, M174-55