

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14, 15, 22 and 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 6 Page(s) 2357)

Set post, cor. to secs. 14, 15, 22 and 23, from which
A Y.Oak 26" dia., bears N.65°W., 36 lks.
A Y.Oak 30" dia., bears N.35°E., 72 lks.
A Y.Oak 15" dia., bears S.22½°W., 202 lks.
A Y.Oak 20" dia., bears S.27 3/4°E., 377 lks.

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey; Clete Putnam - Jan. 1960 - C.S. File 49/42-40

Found - Orig. 20" now 48" B.Oak S.27 3/4°E., 248.8 ft. I open and find good scribing.
Orig. NW and NE BTs now stump holes only.
No trace of orig. SW BT found.
Find 8" x 6" x 12" stone at corner which is under N-S fence.

Set Brass cap at cor. mkd: County Surveyors Office
T 23 S R 5 W
S 15 | S 14
S 22 | S 23
1960

New BTs -24" B.Oak bears N.76°E., 33.7 ft. scribed S14 T23S
R5W CS BT.
15" Laurel bears S.26°E., 25.0 ft. scribed S23 T23S
R5W CS BT.
27" B.Oak bears S.51°W., 82.5 ft. scribed S22 T23S
R5W CS BT.
12" B.Oak bears N.34°W., 84.2 ft. scribed S15 T23S
R5W CS BT.

Fd. OK, DCSO, V. Tracy, Oct. 1969, C.S. File 54/16-58A
FD. brass cap & 2 BTs by D. Edwards 9/2005 - M148-40

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike - 5/23/2007 - C.S. File 67/21-42

Found - 2½" dia., brass cap properly mkd. on 1¼" OD iron pipe, firmly set projects 12" above ground.
Stone, top measures 6"x8" firmly set is found on NE side of BC/IP. No marks noted on stone, did not dig up.
12" Now 19" dia., B.Oak snag, no markings visible on rotting trunk, bears N.34°W., 84.2 ft., agrees w/rec. 1960 BT

continued next page

TOWNSHIP 23 RANGE 05 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14, 15, 22 and 23

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

New -	27" now 38" dia., B.Oak, healed single blaze visible bears S.51°W., 82.5 ft. agrees w/rec. 1960 BT No trace fd. of 1960 NE or SE BTs Orig. 20" dia., B.Oak, now 48" dia., x 10 ft. tall rotted shattered staub, bears S.27¾°E., 248.8 ft. Agrees w/rec. OBT 6" dia., D.Fir double blazed & scribed "X CS" on high blaze & "BT" on low blaze, bears N.30½°W., 14.4 ft. 9" dia., D.Fir double blazed & scribed "T23S R5W S14 CS BT" bears N.16°E., 4.7 ft. 18" dia., D.Fir double blazed & scribed "T23S R5W S23 CS BT" bears S.43½°E., 28.0 ft. Note - Lies on moderate North facing slope in N-S fence line. Compass decl. 16¼°E.
	Fd. BC & 2 BTs 9/2005, D Edwards M148-40 Fd. BC as per DCSO 2007 ren. 5/2013, Todd Catterson; M165-19 Fd as per rec. 12/2020, D Edwards - 2020-0049A&B