

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 35 only, T22-5

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1387)

Set ¼ sec. post, from which
A B.Oak 20" dia., bears N.51°E., 79 lks. dist.
A B.Oak 10" dia., bears N.7°W., 70 lks. dist.

Ben B. Irving, D.C.S. - N.E. Richardson, Loren Weber, crew - Setp. 20, 1940 - C.S. File 16/55

Location identified from orig. BT, N.7°W., 70 lks., down and badly rotted but part of scribe marks visible. Oak stump, N.51°E., 79 lks. dist., other BT, all marks obliterated. Drove a 1½" x 42" Iron pipe 40" in ground for corner, from which
Oak 6" dia., bears N.64°E., 31.0 ft. mkd. ¼ S35 CS BT.
Fir 8" dia., bears N.87°W., 27.0 ft. mkd. ¼ S35 CS BT.

BLM resurvey by James E. Jelley and Wayne L. Rogers, under Group #1119, surveyed 1982 (DCSO records Vol. 46 Page(s) 17666)

The ¼ sec. cor. of sec. 35 only, perpetuated and recorded by Irving in 1940, from original evidence no longer in existence, monumented with an iron pipe, 1¼" dia., firmly set, projecting 4" above ground, from which the remains of bearing trees mkd. by Irving:

An Oak 8" dia., bears N.62¼°E., 46 lks. dist., with healed blaze.

A Fir snag 15" dia., bears N.85¼°W., 40 lks. dist., with scribe marks ¼ S33 BT visible on bark blaze.

At the corner point

Set an aluminum post, 28" long, 2½" dia., 24" in the ground, with alum. cap mkd:

T 22 S R 5 W
1/4 S 35

T 23 S R 5 W

1983

from which a new bearing tree

An Oak 6" dia., bears N.23°W., 61 lks. dist., mkd. ¼ S35 BT.

Fd. OK, Feb. 1994, K. Hoffine, M118-66

Fd. OK, Nov. 1996, K. Hoffine, M126-21

Fd. OK, Aug. 2003, J. Estabrook, M137-66

continued next page

TOWNSHIP 23 RANGE 05 POINT IDENTIFIER # 536700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 35 only, T22-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

DCSO-GIS Corner visitation - 1/4/2006 - Typed: 1/18/2011 -
C.S. File 67/33-1

Monument - 3" alum. cap. Comment - 2 live BTs; 1 snag.