

TOWNSHIP 23 RANGE 05 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25, 26, 35 and 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 6 Page(s) 2347)

Set post, cor. to secs. 25, 26, 35 and 36, from which
A Y.Oak 28" dia., bears S.77°W., 186 lks.
A Y.Oak 15" dia., bears N.74¼°W., 147 lks.
A Y.Oak 20" dia., bears N.51°E., 44 lks.
A Y.Oak 19" dia., bears S.74½°E., 112 lks.

Ben B. Irving, Douglas County Surveyor - Wit: N.E. Richardson and Loren Weber - August 22, 1940 - C.S. File 16/55

Location identified from part of original BT and stump holes of remainder, all which check original field notes.
Set stone 3" x 14" x 18" for corner, from which
Oak 10" dia., bears N.61°W., 66.5 ft. dist.
Fir 12" dia., bears N.63½°E., 61.7 ft. dist.
Laurel 14" dia., bears S.56°E., 60.0 ft. dist.
Fir 28" dia., bears S.46½°W., 107.7 ft. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey; Clete Putnam - Nov. 27, 1959 - C.S. 49/42-26

Found - Oak stump holes that check bearings and distances for orig. SE, NW, and SW BTS.
NE BT in log road.
10" x 2" x 15" stone, chiseled 36, 35, 26 on E W faces at corner.

Ralph Cockerman states this rock has been used for the corner for at least 20 years. He also remembers original SE & NE BTS.

Set Brass cap alongside cor. stone mkd:
County Surveyors Office
T 23 S R 5 W
S26 | S25
S35 | S36
1959

New BTS -9" B.Oak bears N.46°W., 6.0 ft. scribed S26 T23S R5W CS BT.
15" Laurel bears S.31°W., 4.5 ft. scribed S35 T23S R5W CS BT.
12" Laurel bears N.17°E., 29.4 ft. scribed S25 T23S R5W CS BT.
8" R.Fir bears S.71°E., 99.5 ft. scribed S36 T23S R5W CS BT.

continued next page

TOWNSHIP 23 RANGE 05 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25, 26, 35 and 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Mark Smalley - For: Roseburg Resources - Oct./Nov. 2002 - M137-55

Found - 1959 Douglas County Surveyors iron pipe & brass cap
BTs - 18" fir N.8°E., 19.9' healed
15" oak N.46"W., 6.0' healed
23" madrone S.31°W., 4.5' healed
Scribed- 22" oak S.70°W 45.5' "S35 BT"

Fd. BC 7/2018 - By D Edwards, M174-55