

TOWNSHIP 23 RANGE 05 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 23, 24, 25 and 26

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 6 Page(s) 2349)

Set post. cor. to secs. 23, 24, 25 and 26, from which
A Fir 15" dia., bears S.19 3/4°E., 59 lks.
An Alder 16" dia., bears S.41°W., 10 lks.
A Fir 18" dia., bears N.19°W., 35 lks.
A Fir 16" dia., bears N.15°E., 21 lks.

O. F. Thiel - 1901-1909 - C.S. File 64/48 Pg. 14

Set Yew post, along side of old one, from which
A Fir 30" dia., bears N.62°E., 26 lks.

Mark Smalley - For: Roseburg Resources - Oct./Nov. 2002 - M137-55

Set - 5/8"x 48" iron rod and aluminum cap marked "LS 2354 2002" 12" above ground.
17" Fir S.50°E., 40.1' "S25 BT"
15" Maple S.6°E., 12.8' "S25 BT"
22" Fir N.65°W., 19.5' "S23 BT"
26" Fir N.27"E., 9.9' "S24 BT"

DCSO-GIS Corner visitation - 2/7/2007 - Typed: 1/21/2011 - C.S. File 67/33-1

Monument - 2½" al. cap on rebar.
Comment - ok; 4 live BTs