

PRIMARY CORNER DESCRIPTION Sec. Cor. for 11, 12, 13 and 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 6 Page(s) 2351)

Set post, cor. to secs. 11, 12, 13 and 14, from which
A Fir 16" dia., bears N.88°E., 56 lks.
A Fir 15" dia., bears S.50°E., 62 lks.
A Fir 18" dia., bears N.5°W., 88 lks.
A Fir 16" dia., bears S.49°W., 124 lks.

Gene E. Johnson - For: E.A. Hostetler - Oct. 1954 C.S. File 41/318-6 (stamped by A Evens) and M 12-48

Found - Stump of O.B.T., 16" Fir, S.49°W., 124 lks. (face rotted, no scribe visible)
Stump hole of O.B.T., 16" Fir N.88°E., 56 lks.
Set 1/2" iron rod in mound of rock, 3 ft. x 2 ft. high.
Blazed and scribed 4 BTs:
16" Fir N.19°W., 46.9 ft.
6" Madrone N.47°15'E., 47.8 ft.
16" Fir S.60°30'E., 28.6 ft.
14" Madrone S.36°W., 33.0 ft.

Douglas Co. Surveyors Office - Randall Smith, Deputy; Stephen Flause, Terrie Franssen - Dec. 6, 1990 - C.S. File 64/11-5

Found - 1/2" Iron rod protruding 18" above a 3 ft. x 2 ft. high mound of stone.
16" now 14" dia. 1½ ft. high rotted D.Fir stump, no blazes or scribing visible, is found near record position (S.49°W., 81.8 ft.). Possible orig. BT. (BT is approx. 45 ft. below corner, near toe of bluff)
No other original BTs found.
16" now 26" dia. D.Fir with a fully healed double blaze, bears N.19°W., 46.9 ft. (agrees w/rec)
6" now 10" dia. double trunked Madrone with a brass washer mkd. "RE 2741" and possible bark scribing found on SW trunk bears N.47¼°E., 49.5 ft. (Rec. N.47¼°E., 47.8 ft. dist. to washer)
16" now 26" dia. D.Fir with a fully healed double blaze, bears S.60½°E., 30.6 ft. (Rec. S.60½°E., 28.6 ft. dist. a possible face measurement)
SW Madrone from Johnson, is gone.
A Brass cap/iron pipe was not set, ground is too rocky to get a solidly set iron pipe.
New BT - 3" W.Oak double blazed and scribed "X BT" bears S.24°W., 5.4 ft. (Cont. Next Page)

TOWNSHIP 23 RANGE 05 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 11, 12, 13 and 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____


Corner lies at top of rock bluff 12 ft. East of drop off and 10 ft. West of a northerly and easterly running fence corner.

Fd. OK, Sept. 1993, M 119-5

BLM dependent resurvey by Dale T. Bedell, Cadastral Surveyor, under special instructions dated April 30, 1991 under Group No. 1601, surveyed June 1991/July 1992. (DCSO Records Vol. 51 Page(s) 19388-89

The cor. of secs. 11, 12, 13, and 14, perpetuated and recorded by Johnson, in 1954, from original evidence no longer in existence; monumented with an iron rod, ¼" dia., firmly set in a mound of stone, projecting 18" above the ground, from which bearing trees mkd. by Johnson:
A madrone, 18 ins. diam., bears N.49°E., 72 lks. dist., with healed blaze.
A fir, 28 ins. diam., bears S.59 ¾°E., 44 lks. dist., with healed double blaze.
A fir, 25 ins. diam., bears N.15½°W., 71 lks. dist., with healed blaze.
and a bearing tree mkd. by person(s) unknown
An oak, 4 ins. diam., bears S.30°W., 8½ lks. dist., with scribe mark X visible at breast height and BT visible at base.

At the corner point
Set a stainless steel post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock, and in a mound of stone, 3½ ft. base, to top, with brass cap mkd.



Deposit iron rod alongside the stainless steel post.

DCSO-GIS Corner visitation - 11/16/2006 - Typed: 1/21/2011 - C.S. File 67/33-1

Monument - 3" BC/SSP Comment - ok; 4 live BTs

Fd. BC as per BLM 1992 ren. 5/2013, Todd Catterson; M165-19
Fd as per record 3/2024 David Edwards - M183-48
Fd. as per record 4/2024 - D. Edwards - M183-55
Fd. as per record 2/2026 - D. Edwards - M186-68