

TOWNSHIP 23 RANGE 05 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Robert Elder and Henry Gile, Deputy Surveyors,  
under Contract #31 dated April 7, 1853 (DCSO records Vol. 6  
Page(s) 2348)

-----  
Set ¼ sec. post, from which  
    A fir, 6" dia., bears N.5°E., 45 lks.  
    A fir, 14" dia., bears S.53°E., 28 lks.

Mark Smalley - For: Roseburg Resources - Oct./Nov. 2002 -  
M137-55

-----  
Set - 5/8"x 48" iron rod and aluminum cap marked "LS 2354  
2002" 10" above ground.  
    12" Fir N.59°E., 20.3' "¼S BT"  
    21" W.Fir N.18°W., 15.8' "¼S BT"  
    18" W.Fir S.29°W., 57.0' "¼S BT"  
    14" W.Fir S.58°E., 55.6' "¼S BT"  
Corner falls in E-W fence line.

DCSO-GIS Corner visitation - 2/7/2007 - Typed: 1/21/2011 -  
C.S. File 67/33-1

-----  
Monument - 2½" al. cap on rebar. Comment - OK; 4 live BTs