

TOWNSHIP 23 RANGE 05 POINT IDENTIFIER # 640440

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 13

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Dale T. Bedell, Cadastral Surveyor, under special instructions dated April 30, 1991 under Group No. 1601, surveyed June 1991/July 1992. (DCSO Records Vol. 51 Page(s) 19392)

-----  
Point for the center 1/4 sec. cor. of sec. 13, at intersection with the E. and W. centerline.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T23S R5W  
C 1/4  
S 13  
1991

from which

A fir, 12 ins. diam., bears N. 56° E., 64 lks. dist., mkd. C 1/4 S13 BT.

A fir, 10 ins. diam., bears N. 28° W., 40½ lks. dist., mkd. C 1/4 S13 BT.

Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.

David Edwards - For: Roseburg Resources - 3/2024 - M183-48

-----  
Found - BLM brass cap

A 14" Fir stump bears N.56°E., 42.2'.

A 12" Fir with healed blaze bears N.28°W., 26.7'.

New - A 10" dia. Fir scribed "C ¼ S13 BT" bears S.73°E., 25.3.

A 5.5' steel post is set 2' north on line.