

TOWNSHIP 23 RANGE 05 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 12 and 13

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 6 Page(s) 2352)

-----  
Set ¼ sec. post, from which  
A Fir 20" dia., bears S.70°E., 87 lks.  
A Fir 14" dia., bears N.8°W., 29 lks.

Gene E. Johnson - For: E.A. Hostetler - Oct. 1954 - C.S. File 41/318-5 (stamped by A Evens) and M 12-48

-----  
Set ½" Iron rod in mound of rock, 2 ft. x 1 ft. high.  
Blazed and scribed 2 BTs and 3" x 6" Cedar stake.  
22" Fir N.15°W., 72.2 ft.  
28" Fir S.13°30'W., 245.9 ft.  
Corner set by proportional measurement.

Fd. OK, Sept. 1993, M 119-5

BLM dependent resurvey by Dale T. Bedell, Cadastral Surveyor, under special instructions dated April 30, 1991 under Group No. 1601, surveyed June 1991/July 1992. (DCSO Records Vol. 51 Page(s) 19390)

-----  
The 1/4 sec. cor. of secs. 12 and 13, reestablished at proportionate position and recorded by Gene E. Johnson, Registered Engineer No. 3561, in 1954 (Map File 12-48, Douglas County Records), there is no remaining evidence of the original corner, therefore this position is accepted as the corner; monumented with a steel rod, 5/8 in. diam., firmly set, projecting 4 ins. above ground in a collar of stone, from which the bearing trees mkd. by Johnson:  
A fir, 32 ins. diam., bears S.12°W., 369 lks. w/healed double blaze.  
A fir, 26 ins. diam., bears N. 17° W., 110 lks. dist., with healed double blaze.

At the corner point  
Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T23S R5W  
S 12  
1/4 \_\_\_\_\_  
S 13  
1991

Deposit a white "DEEP-1" magnetic marker at base and rebar alongside the stainless steel post.

continued next page

