

TOWNSHIP 23 RANGE 05 POINT IDENTIFIER # 640600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 6 Page(s) 2353)

-----  
Set ¼ sec. post, from which  
A Y.Oak 16" dia., bears S.65°E., 243 lks.  
A W.Oak 20" dia., bears N.80¼°W., 401 lks.

O.F. Thiel - For: Perry Smith - June 1950 (?) - Thiel's book 20 Page 25

-----  
B.Oak 16" S.65°E., 243 lks.  
W.Oak 20" N.80°W., 401 lks.  
Remarked SE tree.  
Marked -Bushy W.Oak, 36 or 20", North, 88½ ft.

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey; Clete Putnam - Jan. 1960 - C.S. File 49/42-47

-----  
Found - Orig. 16" now 46" B.Oak S.65°E., 160.4 ft. I open and find good scribe marks. This tree has been rescribed about 10 years ago.  
No trace of orig. NW BT found.  
Also find 15" x 15" x 12" stone at corner.  
Set Brass cap alongside corner stone marked:  
County Surveyors Office  
T 23 S R 5 W  
¼  $\frac{S \ 1}{S \ 12}$   
1960

New BTs -9" R.Fir bears S.43°E., 117.5 ft. scribed ¼ S12 CSBT  
I find 24" W.Oak bears N.2°E., 90.5 ft., shows good blaze, scribed about 10 years ago.

Fd. OK, Donald Bentz, Sept. 1993, M 119-5  
Fd. OK, Ken Hoffine, Nov. 1996, M 126-22  
Fd Ok by Ken Hoffine 6/1999 M 133-2

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike - 11/28/2006 - C.S. File 67/14-45

-----  
Found BC approx. 2½ ft. East of N-S and W fence line next to large stone. W.Oak bears N.2°E., 90.5 ft. is only BT remaining. 9" R.Fir in now a 24"x5 ft. tall stump orig. BT (Y.Oak, S.65°E., 160.4 ft.) is stump flush with ground. No suitable trees for accessories within reasonable dist. Corner lies on nearly level land in open pasture.