

TOWNSHIP 23 RANGE 05 POINT IDENTIFIER # 700140

PRIMARY CORNER DESCRIPTION 1/4 Cor for Sec. 36; and S. 31, T23-4

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GL0 survey by - James E. Freeman Deputy Surveyor, under Contract #1, dated May, 28, 1851 (DCSO records Vol. 6 Page(s) 2332)

-----  
Set ¼ sec. post, from which  
A Chinquapin 18" dia., bears S.80°E., 24 lks. dist.  
A Fir 30" dia., bears S.15°W., 26 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey; Clete Putnam - Dec. 14-18, 1959 - C.S. File 49/42-29

-----  
Found - Orig. 18" now sec. of Chinquapin snag, S.80°E., 15.8 ft., no scribing found.  
Orig. 30" now 50" Fir stump, center burned. I open from inside, find good scribing "B1", S.15°W., 17.2 ft.  
Large Fir snag, North 50 ft. which is record line tree.

Set Brass cap at cor. mkd: County Surveyors Office  
T 23 S  
R5W ¼ S36|S31 R4W  
1959

Fence 50 ft. West of corner. No live trees near.  
New BTs -60" R.Fir stump bears S.49°E., 53.0 ft. scribed ¼ S31 CS BT.  
70" R.Fir snag bears S.72°W., 34.3 ft. scribed ¼ S36 CS BT, scribed on root section, faces to NE.

Fd. OK, May 1981, R. Quimby, M 79-77