

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19 & 30; 24 & 25, T23-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 376 survey dated Jan. 22, 1881 (DCSO records Vol. 6 Page(s) 2391)

-----

Set Cedar post for cor. secs. 25, 24, 19 and 30, from which  
 A Cedar 10" dia., bears N.40°E., 135 lks.  
 A Fir 8" dia., bears S.2°E., 200 lks.  
 A Fir 8" dia., bears S.80°W., 195 lks.  
 A Fir 10" dia., bears N.30°W., 119 lks.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12652)

-----

The cor. of secs. 19, 24, 25 and 30, determined at record bearing and distance from the only remaining bearing tree:  
 A Fir 32" dia., bears N.30°W., 119 lks. dist., mkd. BT on face of opened blaze.

At the corner point  
 Set an iron post, 3 ft. long, 2" dia., 24" in the ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd:

T23S	
R7W	R6W
<u>S24</u>	<u>S19</u>
S25	S30
1957	

from which  
 A Fir 14" dia., bears N.14°E., 43 lks. dist., mkd. T23S R6W S19 BT.  
 A Fir 20" dia., bears S.64°30'E., 50 lks. dist., mkd. T23S R6W S30 BT.  
 A Fir 29" dia., bears S.9°30'W., 79 lks. dist., mkd. T23S R7W S25 BT.

Fd. OK, BLM survey by Brooks, Group #244, surveyed April/May 1964 (DCSO Records, Vol. 32 Page 13501)

BLM Corrective Dependent Resurvey by Wayne L. Rogers; Boyd W. Peterson; Philip G. Griffin; Dale T. Bedell; Cadastral Surveyors; and Robert H. Browning, Surveying Technician - under Group #'s 1266, 1637 and 1688, - surveyed June 9, 1986/Aug. 22, 1995 - (DCSO records Vol. 51 Page(s) 19505-06)

-----

The Sec. cor. monumented with an iron post, 2 ins. diam., firmly set, projecting 2 ins. above ground, in a collar of stone, with brass cap mkd.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19 & 30; 24 & 25, T23-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>T23S  R7W R6W  S24   S19  S25   S30  1957</p>
<p>from which the remains of an original bearing tree  A sawed fir stump, 48 ins. diam., bears N. 30° W., 119 lks. dist., with fragmentary scribe marks visible on opened blaze.  and the remains of bearing trees mkd. by Gould, Gawron, and Eggen  A broken fir stump, 20 ins. diam., bears N. 36° E., 43 lks. dist., no marks. (Record, N. 14° E.)  A fir, 28 ins. diam., bears S. 72° E., 50 lks. dist., with healed blaze. (Record, S. 64½° E.)  A fir, 40 ins. diam., bears S. 29° W., 79 lks. dist., with healed blaze. (Record, S. 9½° W.)  and new bearing trees  A fir, 25 ins. diam., bears N. 45° E., 21 lks. dist., mkd. T23S R6W S19 BT.  A hemlock, 10 ins. diam., bears N. 59° W., 95 lks. dist., mkd. T23S R7W S24 BT.</p>
<p>Fd. Ok by Bruce Shaner - Nov. 2000 - C. S. File 65/33-12</p>
<p>David Edwards - Crew: Brant Miller &amp; Eric Sprinkle - 9/11/2019 - C.S. File 65/104-5</p> <p style="text-align: center;">-----</p> <p>Found - Standard BLM brass capped iron pipe in good condition.  A 28" dia. Fir snag w/healed blaze bears S.72°E., 33.0'  A 50" dia. Fir with healed blaze bears S.29°W., 52.1'  An 18" dia. Hemlock w/healed blaze bears N.59°W., 62.7'  No other references remain.  New - A 6" dia. Fir scribed "S 19 BT" bears N.70E., 15.8'  Note - Decl. 15° E</p>
<p>2</p>