

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7 & 18; 12 & 13, T23-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by W.H. Byars, Deputy Surveyor under contract # 376 survey dated Jan. 22, 1881 (DCS0 records Vol. 6 Page(s) 2392)

Set Yew post for cor. secs. 13, 12, 7 and 18, from which
A W.Fir 30" dia., bears N.12°E., 31 lks.
A W.Fir 20" dia., bears S.68°E., 39 lks.
A W.Fir 36" dia., bears S.8°W., 49 lks.
A W.Fir 30" dia., bears N.12°W., 28 lks.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCS0 records Vol. 30 Page(s) 12654-55)

The cor. of secs. 7, 12, 13, and 18, determined at record bearing and distance from the original bearing trees:

- A Fir, dead and down, bears N.12°E., 31 lks. dist., marks rotted off.
- A Fir 34" dia., bears S.68°E., 39 lks. dist., mkd. 6W S18 on exposed face of chopped blaze.
- A Fir, dead and down, bears S.8°W., 49 lks. dist., with healed blaze.
- A Fir, dead and down, bears N.12°W., 28 lks. dist., with rotted face.

At the corner point

Set an iron post, 3 ft. long, 2" dia., 26" in the ground, with brass cap mkd:

T23S	
R7W	R6W
S12	S 7
S13	S18
1955	

from which

- A Hemlock 8" dia., bears N.81°E., 49 lks. dist., mkd. T23S R6W S7 BT.
- A Fir 9" dia., bears S.43°E., 56 lks. dist., mkd. T23S R6W S18 BT.
- A W.Fir 14" dia., bears S.30°W., 51 lks. dist., mkd. T23S R7W S13 BT.
- A W.Fir 10" dia., bears N.39°W., 60 lks. dist., mkd. T23S R7W S12 BT.

This corner is established on spur, slopes W.

Douglas Co. Surveyors Office - Milo E. Godfrey and crew - May 8, 1964 - C.S. File 52/102-27

Found - GL0 brass cap, 1957 survey.
(Cont. Next Page)

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7 & 18; 12 & 13, T23-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Dead W.Fir snag bears N.39°W., 39.6 ft., all scribing visible on open blaze.
W.Fir, uprooted and down, bears S.30°W., 33.7 ft., scribing visible.
D.Fir, uprooted and down, bears S.68°E., 25.7 ft. Face down, but old blaze had been chopped open. (Orig. BT)
No other BTs found at present time.
New BTs - 13" W.Fir S.81°W., 30.8 ft. mkd. T23S R7W S13 CSBT
6" W.Fir N.42½°W., 46.8 ft. mkd. S12 CS BT.
8" Hemlock N.84½°E., 42.2 ft. mkd. T23S R6W S7 CSBT
6" W.Fir S.53°E., 79.8 ft. mkd. S18 CS BT.

David Edwards - Oct. 2011 - C.S. File 65/72-35

Found - BLM brass Cap (properly mkd), projecting 4" above ground.
A 13" dia. Hemlock snag w/visible scribe marks bears N.84½°E., 42.2 ft.
A 24" dia W.Fir w/healed blaze bears S.81°W. 30.8 ft
A 19" dia. W.Fir w/healed blaze bears N.42½°W., 46.8 ft.
New BTs- A 14" dia. "W" Fir a scribed "T23S R6W S18 BT" bears S.12°E., 40.0 ft.
A 6 ft. steel post is set 2 ft South, on line.

Dan Baker - For: Rocking "C" Ranch - 12/2014 - M169-13

Found - ¾" BLM brass cap "1957"
25" W.Fir, S.81°W., 30.8' to side center - 1964
16" w.Fir, S.12°E., 40.0' to side center - Edwards
19" W.Fir N.42°W., 46.8' to side center - 1964
New - 14" Hemlock, N.81°E., 31.4' to side center, scribed "T23SR6WS7 BT"

Fd. BC & 4 BTs 5/2021 by D. Baker C.S. file 65/107-9