

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 100540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 7; & 12 of T23-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W.H. Byars, Deputy Surveyor under contract # 376 survey dated Jan. 22, 1881 (DCSO records Vol. 6 Page(s) 2393)

-----  
Set Fir post for ¼ sec. cor., from which  
A Fir 35" dia., bears N.40°E., 22 lks.  
A Laurel 6" dia., bears S.88°W., 24 lks.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12655)

-----  
Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 2" dia., 30" in the ground, with brass cap mkd:

T23S  
¼  
R7W | R6W  
S12 | S 7  
1957

from which

A Fir 7" dia., bears S.21°E., 72 lks. dist., mkd. ¼ S7 BT.  
A Hemlock 7" dia., bears N.49°W., 12 lks. dist., mkd. ¼ S12 BT.

Dan Baker - For: Rocking "C" Ranch - 12/2014 - M169-13

-----  
Found - 3¼" BLM Brass cap "1957"  
27" Fir, S.21°E., 48.1' to spike at side/center, 1957 BLM BT.

27" Hemlock, N.49°W., 8.1' to spike at side/center, 1957 BLM BT.

New - 22" Fir N.49°E., 23.9' to spike at side/center, scribed "¼S7 BT"

12" Fir S.70°E., 23.6' to spike at side/center, scribed "¼S7 BT"

9" Fir, S.62°W., 24.6' to spike at side/center, scribed "¼S12 BT"

BLM resurvey by Joel R Herzberg, Cadastral Surveyor under Group No. 2778 - Surveyed May 2015/July 2016 - (DCSO records Vol 59 Page(s) 23550-1)

-----  
The ¼ sec. cor. of secs. 7 & 12, on the W. bdy. of the Tp., perpetuated by Baker, in 2015, monumented with an iron post, 2" dia., firmly set, projecting 10" above the ground, with brass cap (properly) mkd.

continued next page

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 100540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 7; & 12 of T23-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the BTs mkd. by Gould, et. al., in 1943-57  
A fir, 31" dia., bears S.22 $\frac{3}{4}$ °E., 48.6 ft., with a healed blaze. (Record, S.21°E., 47.5 ft.)  
A hemlock, 28" dia., bears N.49°W., 7.9 ft., with a healed blaze.  
and BTs mkd. by Baker  
A fir, 21" dia., bears N.55 $\frac{3}{4}$ °E., 23.5 ft., with illegible scribe marks visible on partially healed blaze, with a spike right side center.  
A fir, 13" dia., bears S.61 $\frac{1}{4}$ °E., 38.3 ft., with illegible scribe marks visible on partially healed blaze, with a spike right side center.  
A fir, 8" dia., bears S.62 $\frac{3}{4}$ °W., 24.7 ft., with scribe marks  $\frac{1}{4}$  S12 BT visible on partially healed blaze, with a spike right side center.  
A metal fence post is alongside the cor.  
NAD 1983 (2011)  
Latitude: 43° 35' 00.29" N. Longitude: 123° 27' 58.08" W.

Fd. 3 $\frac{1}{4}$ " BLM brass cap 5/2021 - D. Baker - C.S. File 65/107-9