

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 140400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 18 and 19

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 6 Page(s) 2448)

Set Fir post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor., mkd. ¼ S on N. face, from which
A Fir 8" dia., bears N.21°W., 92 lks. dist. mkd. ¼ S BT.
A Hemlock 6" dia., bears S.73°W., 19 lks. dist. mkd. ¼ S BT.

Survey by Wilford N. Haines and Leo J. Martin - For: Harold Woolley and E.G. Whipple, Yoncalla Lumber Co. - April 1957 - RM 1-17 (and Haines field books, H-226 and H-227)

Set 1" x 36" Angle iron with brass cap.
BTs - 10" Fir N.62°W., 34.6 ft.
22" Fir S.33°E., 11.5 ft.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12709-10)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 30" long, 2" dia., 26" in the ground, with brass cap mkd:
T23SR6W
¼ S 18
S 19
1957
from which
A Fir 7" dia., bears N.82°E., 69 lks. dist. mkd. ¼ S18 BT.
A Fir 6" dia., bears S.50°E., 54 lks. dist. mkd. ¼ S19 BT.

Survey by Ken Hoffine for: Lone Rock Timber Co.- Feb. 1993, C.S. File 63/149-13

Found - BLM Brass Cap 0.3 ft. above ground in good condition.
7" D.Fir very old blowdown. Decayed tree with BLM tag on root bears N.82°E., 45.0 ft. to hole.
6" D.Fir rec. S.50°E., 35.6 ft. found no trace, found old BT tag on top of ridge approx. 70 ft. south of corner.
Point for Haines S 1/4 bears N.25°33'E., 19.79 ft. Could not find T-Iron. Used bearing and dist. from Haines BT's.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 18 and 19

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

22" D.Fir stump bears S.33°E., 11.5 ft. Scribing visible. I tag to Haines corner location.
10" D.Fir stump, no marks bears N.62°W., 34.6 ft.
5" D.Fir bears N.34°W., 6.8 ft. from BLM Cap. I blaze and tag.
6" D.Fir bears S.44½°E., 6.2 ft. from BLM Cap. I blaze and tag tree.
Corner lies on 40% north facing side slope approx. 1 chain north of top of flat spur ridge in heavy reprod.

Ken Hoffine - For: Lone Rock Timber Co. - 10/2009 - C.S. File 65/66-40

Found - 1957 BLM cap.
12" D.Fir bears N.46°E. 6.2 ft. (record S.44½°E. 6.2 ft.) healed face and tag
10" D.Fir at record of N.34°W. 6.8 ft. is down and uprooted.
New - 10" D.Fir BT bears S.44½°W., 24.2 ft. we scribe ¼ S19 BT and tag.
16" D.Fir BT bears N.76¼°E. 20.8 ft. we scribe ¼ S18 BT and tag.
Point for Haines quarter corner bears N.25°33'E. 19.79 ft. could not find T-iron computed from bearing and distance of Haines BTs.
22" D.Fir stump bears S.33°E. 11.5 ft. to Haines corner location
Rotten stump remains bears N.62°W., 34.6 to Haines corner location BLM BCIP lies on 40% north facing slope approx. 70 ft. north of top of flat spur ridge in heavy reprod.

BLM resurvey by Joel R Herzberg, Cadastral Surveyor under Group No. 2778 - surveyed May 2015/July 2016 - (DCSO records Vol. 59 Page(s) 23559

The ¼ sec. cor. of secs. 18 & 19, dependently resurveyed by Gould et. al., in 1943-57, and perpetuated by Hoffine, PLS No. 2291, in 1993 and 2009, monumented with an iron post, 2" dia., projecting 4" above the ground, with brass cap (properly) mkd.
from which the remaining BT mkd. by Hoffine, in 1993
A fir, 15" dia., bears S.45¾°E., 6.0 ft., with a healed blaze.
and the remains of BTs mkd. by Hoffine, in 2009
A fir stump, 17" dia., bears N.75¾°E., 21.1 ft., with marks S 4 and other illegible scribe marks visible on partially healed blaze. continued next page

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 140400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 18 and 19

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

A fir, 13" dia., bears S.44 $\frac{3}{4}$ °W., 24.1 ft., with illegible scribe marks visible on partially healed blaze. Corner is located on a N. facing slope, approximately 70 ft., N., of the top of flat spur ridge.
Note: The point established for the $\frac{1}{4}$ sec. cor. of secs. 18 and 19 by Haines, PLS No. 239, in 1957, was searched for but not recovered.

NAD 1983 (2011)
Latitude: 43°33'43.62" N. Longitude: 123°27'07.19" W.