

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 18

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 6 Page(s) 2451-52)

-----  
Set Dogwood post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor., mkd. ¼ S on N. face, from which  
A Fir 10" dia., bears S.18°E., 92 lks. dist. mkd. ¼ S BT.  
A Laurel 8" dia., bears N.21°W., 17 lks. dist. mkd. ¼ S BT

Survey by Wilford N. Haines - For: Harold Woolley and E.G. Whipple, Yoncalla Lumber Co. - April 1957 - RM 1-17 (and Haines field books, H-226 and H-227)

-----  
Set 1" x 36" Angle iron with brass cap.  
BTs - 26" Fir N.06°E., 16.4 ft.  
20" Fir N.27°W., 45.0 ft.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12712)

-----  
Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30" long, 2" dia., 26" in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd:

T23SR6W  
¼  $\frac{S \ 7}{S \ 18}$   
1957

from which

A Fir 26" dia., bears N.5°W., 22 lks. dist. mkd. ¼ S7 BT.

A Fir 6" dia., bears S.35°E., 90 lks. dist. mkd. ¼ S18 BT

This cor. monument is established on spur, slopes N.80°E.

Ken Hoffine - For: Lone Rock Timber Co. - 10/2009 - C.S. File 65/66-40

-----  
Found - 1957 BLM cap.

Haines T-Iron bears S.20°14'W., 21.67 ft.

32" D.Fir bears N.8°W., 14.5 feet (record N.8°W., 14.52 feet) healed face and tag

24" D.Fir bears S.36°E. 60.5 ft (record S.35°E. 59.40 ft) healed face and tag

31" D.Fir bears S.56½°W., 7.2 ft bark scribed this is a BT for Haines T-Iron

BLM BCIP lies on steep spur ridge.

continued next page

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 18

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM resurvey by Joel R Herzberg, Cadastral Surveyor under Group No. 2778 - surveyed May 2015/July 2016 - (DCSO records Vol. 59 Page(s) 23561-2

-----  
The ¼ sec. cor. of secs. 7 & 18, monumented with an iron post, 2" dia., firmly set, projecting 10" above the ground, with brass cap (properly) mkd.

from which the BTs mkd. by Gould, et. al., in 1943-57

A fir, 26" dia., bears S.35°E., 59.4 ft., with a healed blaze.

A fir, 33" dia., bears N.5°W., 14.5 ft., with a healed blaze.

and BTs mkd. by Haines, in 1957

A fir, 32" dia., bears S.56½°W., 7.1 ft., with scribe marks ¼ 363 visible on bark blaze.

A fir, 25" dia., bears N.57¼°W., 35.3 ft., with scribe marks ¼ S 363 visible on bark blaze.

Note: the BTs mkd. by Haines now reference the cor. reestablished by Gould, et. al.

From this cor., a point erroneously reestablished for the ¼ sec. cor. of secs. 7 & 18, by Haines, in 1957, bears S.20°04'16"W., 21.67 ft., and was not accepted for the cor., and now functions as a reference monument, monumented with a "T" iron, ¾" dia., firmly set, projecting 2" above the ground, with a brass washer mkd. WILFORD N HAINES 239 SURVEY POINT DRAIN ORE.

Corner is located on a steep spur ridge, bears N.5°W. & S.5°E.