

PRIMARY CORNER DESCRIPTION Standard ¼ cor. Sec. 6 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1429)

Set standard ¼ sec. post, from which
A Fir 14" dia., bears S.57°E., 22 lks. dist.
A Fir 24" dia., bears S.37°W., 75 lks. dist.

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Special Instructions dated Oct. 27, 1897 (DCSO records Vol. 4 Page(s) 1467)

The standard ¼ sec. cor. destroyed. I reestablish this cor. from the bearing tree bearing S.57°E., from the cor. 22 lks. dist. as follows:
Set a Fir post, 3 ft. long, 4" sq., 24" in the ground, mkd. S C ¼ S on S. face; from which
A Fir 24" dia., bears S.57°E., 22 lks. dist., mkd. SC ¼ S BT.
An Alder 7" dia., bears S.7°W., 91 lks. dist., mkd. SC ¼ S BT.

Douglas Co. Surveyors Office - Ben B. Irving, Deputy - crew, N.E. Richardson; Fred Southwick - Sept. 18-19, 1930 - C.S. File 37/31 (and "old" cor. book, page 37)

Location identified from orig. BTs as follows:
14" Fir snag, S.47°E., 22 lks. (Rec. S.57°E.)
30" Fir S.37°W., 75 lks. lks. (Both scribed S.C. ¼S BT)
Remarked:
30" Fir S.C. ¼ S6 CS BT.
Blazed and scribed:
30" Fir S.47°E., 29 lks. S.C. ¼ S6 CS BT.
Set 4" x 36" Cedar post for corner.

Wilford N. Haines #239 - For: Irvin Rice and Whipple Mill - 1954-55 - C.S. File 42/13 (M 112-74)

Found a scribed stake and two bearing trees.
At point for corner set an angle iron with brass cap inscribed "Survey point - Wilford N. Haines #239".

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12632)

The standard ¼ sec. cor. of sec. 6 only, determined at record bearing and distance from the remains of the original bearing trees:
(Cont. Next Page)

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 140700

PRIMARY CORNER DESCRIPTION Standard ¼ cor. for Section 6 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A Fir 35" dia., bears S.52°E., mkd. SC ¼ S6 CS BT.
A Fir stump 55" dia., bears S.39°W., mkd. SC ¼ S6 CSBT.
At the corner point
Set an iron post, 3 ft. long, 1" dia., 27" in the ground, and
in a mound of stone, 3 ft. base, to top, with brass cap mkd:

¼ S 6
S C
1955

from which

A Fir 10" dia., bears S.13°E., 30 lks. dist., mkd. ¼ S6 SC
BT.

A Chinquapin 7" dia., bears S.34°W., 51 lks. dist., mkd.
¼ S6 SC BT.

Fd. OK, Oct. 1990, C.S. File 63/127-15