

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 171700

PRIMARY CORNER DESCRIPTION C C for Secs. 31 & 32, T22-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Jack Heritage, V. Perron, crew - Dec. 23, 1969 - C.S. 49/143-99

Found - 1955 Cadastral brass cap, nearly out of ground, properly mkd., with Haines T-Iron alongside.
18" Fir N.36½°W., 45.4 ft., now dead, scribe visible, overgrowth of 9 rings. Haines BT
24" Fir stump N.20°E., 48.1 ft., scribe visible. Haines BT. (Cont. Next Page)
Orig. Cedar BT gone. Stumphole and turned out tree to NW still in evidence.

We Reset Brass Cap.

New BT - 12" Hemlock N.6°W., 47.8 ft. mkd. T22S R6W S31 CC CS BT.

No trees close to NE. This corner lies on very steep northerly slope about 350 ft. South of Squaw Creek.

Survey by Ken Hoffine, L.S. #2291 - Gary Aniolet, wit. - For: Lone Rock Timber Co. - March/Nov. 1990 - C.S. File 63/127-5

Found - Corner is a GLO brass cap with Haines T-Iron alongside. Corner is loosely set in rock.
12" W.Fir (Rec. Hemlock) bears N.6°W., 47.6 ft., well healed face and BT tag.

New BT - Put Lone Rock Timber location tag on 6" D.Fir bearing N.60°E., 24.4 ft.

Painted faces and wrote BT on tree trunks of BTs with florescent orange paint. Cor. lies on steep N. slope near rock face with pile of rocks around corner and Haines T-Iron alongside. Small stand of 20-40" timber to the NW and Squaw Creek bears North approx. 165 ft.

Fd. OK, March 1991, M 111-72