

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 200100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 31 & 32; 5 & 6, T24-6

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 6 Page(s) 2389-90)

-----  
Set post cor. to secs. 5, 6, 31 and 32, from which  
A Fir 15" dia., bears N.22°E., 53 lks.  
A Fir 16" dia., bears N.62°W., 60 lks.  
A Fir 10" dia., bears S.57°W., 8 lks.  
A Fir 10" dia., bears S.47°E., 10 lks.

GL0 survey by William R. Whipple, Deputy Surveyor, under Contract #577, dated July 18, 1891 (DCSO records Vol. 8 Page(s) 3180) (Fd. OK on Pages 3190-91)

-----  
The Sec. cor., I reestablished by setting a cedar post, 4 ft. long, 4" sq., 24" in the ground, mkd. T23S S32 on NE.; T24S S5 on SE.; R6W S6 on SW.; and S31 on NW. face with 6 notches on S and 5 notches on E. edges, from which original bearing trees  
A Fir 15" dia., bears N.22°E., 53 lks. dist., mkd. T23S R6W S32 BT.  
A Fir 10" dia., bears S.47°E., 10 lks. dist., mkd. T24S R6W S5 BT.  
A Fir 10" dia., bears S.57°W., 8 lks. dist., mkd. T24S R6W S6 BT.  
A Fir 16" dia., bears N.62°W., 60 lks. dist., mkd. T23S R6W S31 BT.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12648)

-----  
The Sec. cor., determined at record bearing and distance from the only remaining bearing tree:  
A Fir 24" dia., bears N.22°E., 53 lks. dist., mkd. BT on open blaze.

At the corner point  
Set an iron post, 3 ft. long, 2" dia., 30" in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd:

T23SR6W  
S31 | S32  
S 6 | S 5  
T24S  
1957

from which  
A Hemlock 12" dia., bears S.63°E., 35 lks. dist., mkd. T24S R6W S5 BT.

(Cont. Next Page)

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 200100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 31 & 32; 5 & 6, T24-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Hemlock 8" dia., bears S.30°W., 17 lks. dist., mkd. T24S  
R6W S6 BT.  
A Fir 30" dia., bears N.74°W., 57 lks. dist., mkd. T23S  
R6W S31 BT.

Fd. and Used in BLM Corrective Dependent Resurvey by Wayne L. Rogers; Boyd W. Peterson; Philip G. Griffin; Dale T. Bedell; Cadastral Surveyors; and Robert H. Browning, Surveying Technician - under Group #'s 1266, 1637 and 1688, - surveyed June 9, 1986/August 22, 1995 - (DCS0 records Vol 51 Pg 19451)

Mark Smalley - for: Roseburg Forest Products - Dec. 4, 1996  
- C.S. 65/15-6F

-----  
Found - 1957 GLO I.P.B.C.  
16" Hemlock, S.3°W., 17 lks. good scribe visible  
40" Fir, S.74°W., 57 lks. good healed face. (Diagram shows and rec is NW not SW. Added 6/14/2010)  
16" Hemlock, S.63°E., 35 lks., fair visible scribe  
27" Fir, N.22°E., 53 lks., poor, visible scribe  
New Accessories -  
8" Hemlock, S.74°W., 25.1' scribed "S6 BT"  
11" Hemlock, S.7°W., 20.9' scribed "S6 BT"

Robert Ward - Ron Rice & Josh Reed, crew - June 2010 - C.S. File 65/69-30

-----  
Found - BLM Brass Cap (properly marked) dated 1957 with the following Accessories;  
30" Fir bears N.22°E., 35.0' open face.  
18" Hemlock bears S.63°E., 23.1' healed face blow down.  
17" Hemlock bears S.30°W., 11.2' rotted face.  
40" Fir bears N.74°W., 37.6' healed face.  
13" Hemlock bears S.20°W., 20.6' healed face

Ronald L Rice - Cody Kievit - Jan. 2016 - C.S. File 65/93-6

-----  
Found - BLM brass cap dated 1957  
17" Hemlock stump bears S.30°W., 11.2' - rotted face  
40" D.Fir metal capped stump bears N.74°W., 37.6', healed face  
13" Hemlock stump bears S.20°W., 20.6' - healed face  
New - Corner falls in recently logged area.  
No new accessories established.  
Set 60D nail at side center of all bearing tree stumps.  
continued next page

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 200100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 31 & 32; 5 & 6, T24-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Added galvanized sheet metal cap to NW bearing tree stump as noted above.  
Note - Corner has steel post adjacent to it.  
All BTs have red painted bands and yellow tags.  
Compass Declination 16° East

Daniel A Renton, Minister-Glaeser Surveying - Garrett Finch & Crew - For: US Department of Interior, BLM - Mean Mustard & Galagher Canyon 1- Task A -July 2023 - M185-5 A-D  
-----  
Found - 3/4" GLO brass cap (properly mkd), 0.4' above ground from which:  
A 19" stump (6' high) bears S.30°W., 12.0 ft with healed blaze, BT and Roseburg Timber sign and side nail (2010)  
A 12" stump (6' high) bears S.18°W. 21.1 ft with healed blaze, Roseburg Timber sign & side nail (2010)  
A 36" stump (6' high) bears N.65°W., 37.6 ft with healed blaze Roseburg Tmbr sign & metal top (2016)  
(Set chaining nail at side center, BT signs on front and rear, and painted red band for existing BTs)  
New - A 5/8" iron rod w/2" alum cap bears S.45°E., 15.0 ft  
A 5/8" iron rod w/2" alum cap bears S.45°W., 15.0 ft  
A 5/8" iron rod w/2" alum cap bears N.45°W., 15.0 ft  
A 5/8" iron rod w/2" alum cap bears N.45°E., 15.0 ft