

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 18

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 6 Page(s) 2449)

Set Hemlock post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S on W. face, from which
A Fir 12" dia., bears N.29°W., 45 lks. dist. mkd. ¼ S BT
A Fir 36" dia., bears S.61½°E., 8 lks. dist. mkd. ¼ S BT

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12710-11)

The ¼ sec. cor. of secs. 17 and 18, determined at record distance from the original bearing trees:

A Fir 20" dia., bears S.28°E., 8 lks. dist. mkd. ¼ S BT.
(Record bearing S.62½°E.)

A Fir 50" dia., bears N.80°W., 45 lks. dist. mkd. with a chopped out blaze. (Record bearing N.20°W.)

At the corner point

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:

T23SR6W
¼
S18|S17
1957

from which

A Fir 14" dia., bears S.87½°E., 44 lks. dist. mkd. ¼ S17 BT.

A Fir 28" dia., bears N.72°W., 95 lks. dist. mkd. ¼ S18 BT.

Lone Rock Timber Co. - Ken Hoffine, surveyor - Gary Angiolet, Ignacio Roman & Dan Sailey, witnesses - 8/25/2011 - C.S. File 65/72-39

Found - 1957 GLO brass cap (properly) mkd.
28" D.Fir bears N.73°W., 63.25 ft. (rec. N.72°W., 62.7 ft.) Healed face and BT tag.

New - 10" D.Fir bears S.65¾°E., 18.8 ft. We scribe ¼ S17 BT & tag tree.

Note - Lone Rock ran a random closed loop conventional survey from the S ¼ to the NE sec. corners of Sec. 18, to blaze & paint true line for timber management purposes. We located the above monument during the course of this survey.