

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7, 8, 17 and 18

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 6 Page(s) 2449)

 Set a Cedar post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 7, 8, 17 and 18, mkd. T23S S8 on NE.; R6W S17 on SE.; S18 on SW.; and S7 on NW. faces, with 4 notches on S. and 5 notches on E. edges, from which
 A Laurel 24" dia., bears N.33°E., 44 lks. dist. mkd. T23S R6W S8 BT.
 A Laurel 8" dia., bears S.70°E., 10 lks. dist. mkd. T23S R6W S17 BT.
 A Laurel 6" dia., bears S.12°W., 9 lks. dist. mkd. T23S R6W S18 BT.
 A Laurel 36" dia., bears N.22°W., 19 lks. dist. mkd. T23S R6W S7 BT.

Survey by Wilford N. Haines - For: Harold Woolley and E.G. Whipple, Yoncalla Lumber Co. - April 1957 - RM 1-17 (and Haines field books, H-226 and H-227)

 Set 1" x 36" Angle iron with brass cap.
 BTs - 10" Fir N.34°30'W., 49.0 ft.
 16" Fir S.60°30'W., 20.0 ft.
 24" Fir S.52°E., 15.0 ft.
 14" Fir N.52°E., 11.5 ft.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12711)

 Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
 Set an iron post, 30" long, 2" dia., 14" in the ground to bedrock, over a 4" cross chiseled in the bedrock, in a mound of stone 5 ft. base, to top, with brass cap mkd:

T23SR6W	
S 7	S 8
S18	S17
1957	

from which
 A Fir 14" dia., bears N.19°E., 46 lks. dist. mkd. T23S R6W S8 BT.
 A Fir 16" dia., bears S.64°E., 67 lks. dist. mkd. T23S R6W S17 BT.
 A Fir 12" dia., bears S.26°W., 34 lks. dist. mkd. T23S R6W S18 BT.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7, 8, 17 and 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A Fir 12" dia., bears N.14°W., 57 lks. mkd. T23S R6W S7 BT
This cor. is established at head of ravine, course NE.

Fd. March 1990, C.S. File 63/104-55&56
Fd. Feb. 1993, K Hoffine, C.S. File 63/149-13

Lone Rock Timber Co. - Ken Hoffine, surveyor - Gary Angiolet,
Ignacio Roman & Dan Sailey, witnesses - 8/25/2011 - C.S. File
65/72-39

Found - 1957 GLO brass cap (properly) mkd.
Haines T-iron bears S.16¼°E., 15.25 ft.
24" D.Fir bears N.16°E., 28.6 ft. (rec. N.19°E.,
30.36 ft.) healed face & BT tag.
16" D.Fir bears S.64¼°E., 44.3 ft. (rec. S.64°E.,
44.22 ft.) healed face & BT tag.
20" D.fir bears N.44°W., 33.9 ft. to GLO cap (This
BT is for Haines T-iron)
34" D.Fir stump bears S.32¾°E., 30.0 ft. to GLO cap
(This is a BT for Haines T-iron)

Note - Lone Rock ran a random closed loop conventional
survey from the S ¼ to the NE sec. corners of
Sec. 18, to blaze & paint true line for timber
management purposes. We located the above
monument during the course of this survey.

BLM resurvey by Joel R Herzberg, Cadastral Surveyor under
Group No. 2778 - surveyed May 2015/July 2016 - (DCSO records
Vol. 59 Page(s) 23560-1

The cor. of secs. 7, 8, 17, & 18, monumented with an iron
post, 2" dia., firmly set, projecting 10" above the ground,
with brass cap (properly) mkd.
from which the remains of the BTs mkd. by Gould, in 1943-57
A fir, 25" dia., bears N.15½°E., 28.6 ft., with a healed
blaze. (Record, N.19°E., 30.4 ft.)
A fir snag, 12" dia., bears S.64°E., 44.2 ft., with no
marks visible on partially healed blaze
A decayed fir stump, 17" dia., bears S.26°W., 24.5 ft.,
with a healed blaze. (Record, 22.4 ft.)
and the remains of the BTs mkd. by Haines, in 1957
A decayed fir stump, 33" dia., bears S.32¾°E., 29.9 ft.,
with scribe marks 23S R6W visible on bark blaze.
A decayed fir stump, 34" dia., bears S.25½°W., 28.0 ft.,
with scribe marks S R6W 18 visible on bark blaze.
A fir, 20" dia., bears N.44°W., 34.1 ft., with a ¾" dia.
brass tag mkd. 239 SURVEY POINT nailed to the face of
healed blaze. continued next page

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7, 8, 17 and 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Note: the BTs mkd. by Haines now reference the cor. reestablished by Gould, et. al. and new bearing trees

A fir, 30" dia., bears S.77 $\frac{3}{4}$ °E., 52.4 ft., mkd. T23S R6W S17 BT.

A fir, 6" dia., bears S.4 $\frac{1}{2}$ °W., 19.6 ft., mkd. X at breast height and BT at base.

From this cor., a point erroneously reestablished for the cor. of secs. 7, 8, 17, & 18, by Haines, in 1956, bears S.16°04'15"E., 15.05 ft., and was not accepted for the cor., and now functions as a reference monument, monumented with a "T" iron, $\frac{3}{4}$ " dia., firmly set, projecting 14" above the ground, with a brass washer mkd. WILFORD N HAINES 239 SURVEY POINT DRAIN ORE.