

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 6 Page(s) 2452)

Set Cedar post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor., mkd. ¼ S on W. face, from which
A Fir 20" dia., bears N.31°E., 16 lks. dist. mkd. ¼ S BT.
A Fir 5" dia., bears S.17°W., 73 lks. dist. mkd. ¼ S BT.

Survey by Wilford N. Haines and Leo J. Martin - For: Harold Woolley and E.G. Whipple, Yoncalla Lumber Co. - April 1957 RM 1-17 (and Haines field books, H-226 and H-227)

Set 1" x 36" Angle iron with brass cap.
BTs - 22" Cedar N.27°W., 10.3 ft.
16" Cedar S.86°E., 6.5 ft.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12713)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30" long, 2" dia., 28" in the ground, with brass cap mkd:

T23SR6W
¼
S7|S8
1957

from which

A Hemlock 6" dia., bears N.22°E., 40 lks. dist. mkd. ¼ S8 BT.

A Cedar 6" dia., bears S.55°W., 48 lks. dist. mkd. ¼ S7 BT

BLM resurvey by Joel R Herzberg, Cadastral Surveyor under Group No. 2778 - surveyed May 2015/July 2016 - (DCSO records Vol. 59 Page(s) 23562)

The ¼ sec. cor. of secs. 7 & 8, monumented with an iron post, 2" dia., firmly set, projecting 11" above the ground, with brass cap (properly) mkd.

from which remains of the BTs mkd. by Gould, in 1943-57

A decayed hemlock stump, size indeterminate, bears N.22°E., 26.4 ft., with illegible scribe marks visible on partially opened blaze.

A cedar, 28" dia., bears S.70¼°W., 31.7 ft., with a healed blaze. (Record, S.55°W.)

and bearing trees mkd. by Haines, in 1957

continued next page

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 200540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 8

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

A cedar, 34" dia., bears East, 24.1 ft., with a healed blaze.

A cedar, 30" dia., bears S.74½°E., 36.0 ft., with a healed double blaze.

Note: the BTs mkd. by Haines now reference the cor. reestablished by Gould, et. al.

From this cor., a point erroneously reestablished for the 1/4 sec. cor. of secs. 7 and 8, by Haines, in 195, bears S.72°52'21"E., 30.20 ft., and was not accepted for the cor., and now functions as a reference monument, monumented with a "T" iron, 3/4" dia., firmly set, projecting 8" above the ground, with a brass washer mkd. WILFORD N HAINES 239 SURVEY POINT DRAIN ORE.

Corner is located on a SW. slope.