

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Wilford Haines - For: Rice & Whipple - Surveyed 1954 & 1955  
(Rec'd map 2/27/1981) - M112-74 & C.S. File 42/13

-----  
Set - Brass cap inscribed, Survey Point - Wilford N Haines  
#239

9" D.Fir N.44°W., 12.1 ft.

7" D.Fir S.69°E., 2.3 ft.

Note - This info added to the report 11/13/2003, JC DCSO

-----  
Douglas Co. Surveyors Office - R.B. Kimberling, Peter Earle,  
crew - March 2, 1978 - C.S. File 59/46-38

-----  
Found - A 1" T-Iron with 1" brass cap set 3" above ground  
mkd. "Wilford N. Haines 239 Survey Point, Drain,  
Oreg."

A 9" Fir with Haines' washer, is down, broken stump  
bears N.44°W., 12.1 ft. with scribing "1/16 S6  
BT" on single blaze.

A 7" Fir is down, broken stump bears S.69°E., 2.3  
ft. with scribing "1/16 S BT" in single blaze.

Set a 1" I.P. with brass cap set 6" above ground and mkd.  
"Douglas County Surveyor T23S R6W S 1/16 S6 S5 1978". I  
place Haines' T-Iron/brass cap under North lip of DCSO brass  
cap.

New BTs -10" W.Fir bears N.34°W., 92.2 ft., I double blaze  
and mark "S 1/16 S6 CS BT".

6" W.Fir bears N.55°E., 26.9 ft., I double blaze and  
mark "S 1/16 S5 CS BT".

Corner is at East edge of clearcut unit, at top of steep  
climb, 1/4 mile North of Brush Creek Road.

-----  
Ken Hoffine - For: Lone Rock Timber Co. - 10/22/2003 - C.S.  
File 65/48-39

-----  
Found - 1978 Douglas Co. brass cap with Haines T-iron under  
north lip of cap.

Set - 5/8"x40" iron rod with yellow plastic cap marked  
Lone Timber PLS 2291, bears N.46°E., 30.4 ft.

13" D.Fir bears N.37°W., 40.1 ft., we scribe S 1/16  
S6 BT

25" W.Fir bears S.9¾°E., 20.0 ft. old scar - no rec.

Note - Corner lies on flat bench just North of edge of  
steep slope ≈ 180 ft to BLM Road #23-6-6.3. S1/16  
lies N.12°30'W., 1660.99 ft. from the SE section  
cor. of sec. 6.

Dec. 19½°