

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Section 20

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

BLM Resurvey - James E Jelley, Wayne L. Rogers, and Lance J. Bishop, Cadastral Surveyors Under Group # 1098 - Surveyed June 1982/Nov. 1983 (DCSO records Vol. 46 Page(s) 17737)

Point for the center 1/4 sec. cor. of sec. 20, at intersection with the E. and W. center line.

Set an aluminum post, 28" long, 2½" dia., 24" in the ground, with alum. cap mkd:

T 23 S R 6 W
C 1/4
S 20
1983

from which

A Fir 18" dia., bears S.66°W., 24 lks. dist. mkd. X BT.

A Fir 20" dia., bears N.39½°W., 10 lks. dist. mkd. C ¼ S20 BT.

BLM Corrective Dependent Resurvey by Wayne L. Rogers; Boyd W. Peterson; Philip G. Griffin; Dale T. Bedell; Cadastral Surveyors; and Robert H. Browning, Surveying Technician - under Group #'s 1266, 1637 and 1688, - surveyed June 9, 1986/Aug. 22, 1995 - (DCSO records Vol. 51 Page(s) 19507-08)

Point for the center ¼ sec. cor. of sec. 20, at intersection with the E. and W. centerline.

From this point, the center ¼ sec. cor. of sec. 20, erroneously established by Jelley, Rogers, and Bishop in 1982-83, bears S. 52° 19' 30" W., 0.227 chs. dist.; monumented with an aluminum post, 2½ ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap marked and witnessed as described in the official record except the NW. bearing tree is uprooted. Remove the aluminum post, destroy the marks on the uprooted bearing tree, and at the true corner point:

Reset the aluminum post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, to solid rock, in a collar of stone, with aluminum cap mkd.

T23S R6W
C¼ S20
1994

from which a bearing tree mkd. by Jelley, Rogers, and Bishop

A fir, 23 ins. diam., bears S. 76° W., 26 lks. dist., with healed blaze.

and a new bearing tree

(Cont. Next Page)

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 240340

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. of Sec. 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 22 ins. diam., bears N. 18½° E., 15½ lks. dist.,
mkd. X at breast height and BT at the base.

Deposit a white "DEEP-1" magnetic marker at the base of the
aluminum post.