

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 17 and 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 6 Page(s) 2447)

Set Yew post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor., mkd. ¼ S on N. face, from which
A Laurel 6" dia., bears N.12°E., 10 lks. dist. mkd. ¼ S BT
A Chinquapin 8" dia., bears S.31°W., 13 lks. dist. mkd. ¼ S BT.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12708)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 2" dia., 24" in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T23SR6W
¼ $\frac{S\ 17}{S\ 20}$
1957

from which

A Cedar 12" dia., bears N.32°W., 25 lks. dist. mkd. ¼ S17 BT.

A Fir 15" dia., bears S.56½°E., 56 lks. dist., mkd. ¼ S20 BT.

Cor. Fd. and used in BLM subd. of sec. 20, by Jolley, Rogers and Bishop, Contract #1098, surveyed June 1982/Nov. 1983 (DCSO records, Vol. 46 Page 17738)

David Edwards - For: Roseburg Resources - June 2016 - M172-12

Found - BLM brass cap (1957)
17" dia., fir snag bears S.56½°E., 35.0 ft. 1957
24" dia., fir bears N.32°W., 16.5 ft. 1957
Both with healed blaze.

New BT - 8" dia., Hemlock scribed "¼ S20 BT" bears S.29°E., 23.6 ft.

Note - 6 ft steel posts are set 2 ft S.20°W., and S.88°E., 2 ft.