

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 17

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 6 Page(s) 2450)

 Set Hemlock post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S on N. face, from which
 A Fir 24" dia., bears N.30°E., 38 lks. dist. mkd. ¼ S BT.
 A Fir 20" dia., bears S.21°W., 35 lks. dist. mkd. ¼ S BT.

Survey by Wilford N. Haines and Leo J. Martin - For: Harold Woolley and E.G. Whipple, Yoncalla Lumber Co. - April 1957 - RM 1-17 (and Haines field books, H-226 and H-227)

 Set 1" x 36" Angle iron with brass cap.
 BTs - 36" Fir N.35°E., 10.6 ft.
 28" Fir S.43°E., 17.0 ft.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12711-12)

 Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
 Set an iron post, 30" long, 2" dia., 24" in the ground, with brass cap mkd:
 T23SR6W
 ¼ $\frac{S \ 8}{S \ 17}$
 1957

from which
 A Chinquapin 6" dia., bears N.4°E., 70 lks. dist. mkd. ¼ S8 BT.
 A Fir 6" dia., bears S.88°W., 14 lks. dist. mkd. ¼ S17 BT

BLM resurvey by Joel R Herzberg, Cadastral Surveyor under Group No. 2778 - surveyed May 2015/July 2016 - (DCSO records Vol. 59 Page(s) 23559-60)

 The ¼ sec. cor. of secs. 8 & 17, dependently resurveyed by Gould et. al., in 1943-57, monumented with an iron post, 2" dia., firmly set, projecting 12" above the ground, with brass cap (properly) mkd.
 from which the remains of the BTs mkd. by Haines, in 1957
 A fir stump with a tin cap, 30" dia., bears N.8¾°E., 7.5 ft., with no marks visible.
 A fir, 35" dia., bears S.23½°E., 15.5 ft., with fragmentary scribe marks visible and a brass tag, 3/4" dia., mkd. 239 SURVEY POINT on a bark blaze.

continued next page

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Note: the BTs mkd. by Haines now reference the cor. reestablished by Gould, et. al., in 1934-57. and a new bearing tree

A fir, 13" dia., bears N.52°E., 25.8 ft., mkd. ¼ S8 BT. There is no remaining evidence of the bearing trees mkd. by Gould et. al., in 1943-57.

From this cor., the point erroneously established for the ¼ sec. cor. of secs. 8 & 17 by Haines, in 1955, bears N.17°03'00"W., 5.10 ft., and was not accepted for the cor., and now functions as a reference monument, monumented with a "T" iron, ¾" dia., firmly set, projecting 15" above the ground, with a brass washer mkd. WILFORD N HAINES 239 SURVEY POINT DRAIN ORE,

Ken Hoffine, Lone Rock Timber Management - Gary Angiolet - 2/21/2017 - C.S. File 65/95-42

Found - 1957 BLM BC, properly marked
We did not locate any 1957 USBLM record BTs
Haines T-Iron bears S.71°32'39"W, 5.07 ft.
Rotten stump bears N.8¼°E., 7.6 ft. to BLM monument (this is also a Haines BT to his T-Iron N.33°E., 10.8 ft. rec. N.35°E., 10.6 ft.)
33" Fir bears S.23½°E., 15.4 ft (BT tag calls N.27°W., 15.0 ft.) This is also a Haines BT to his T-Iron S.41¼°E., 16.6 ft. record S.43°E., 17.0 ft.)
14" Fir of unknown origin bears N.86½°E., 21.5 ft. BT tag calls S.87°W., 21.3 ft. Healed face.

Note - We ran a random transit traverse beginning at the SE corner of Sec. 8, to the S¼ Corner, then continued to the SW corner of Sec. 8. We marked property boundaries on true line between corners. We find the record 1957 BLM brass caps and Haines T-Iron's at all corner. We closed our conventional survey with GPS.