

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 240600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 6 Page(s) 2453-54)

Set Cedar post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S on N. face, from which
A Maple 8" dia., bears N.12°E., 50 lks. dist. mkd. ¼ S BT
A Willow 6" dia., bears S.24°W., 18 lks. dist. mkd. ¼ S BT

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12714)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 2" dia., 26" in the ground, and in a mound of stone, 6 ft. base, to top, with brass cap mkd:

T23SR6W

¼ $\frac{S 5}{S 8}$

1957

from which

A Hemlock 12" dia., bears N.7°W., 41 lks. dist. mkd. ¼ S5 BT.

A Cedar 12" dia., bears S.13°E., 12 lks. dist. mkd. ¼ S8 BT.

Fd. Ok, Feb. 1993, K. Hoffine, C.S. File 63/149-6