

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. Section 5 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1428)

Set standard ¼ sec. post, from which
A Hemlock 15" dia., bears S.28½°E., 29 lks. dist.
A Maple 18" dia., bears S.31°W., 20 lks. dist.

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Special Instructions dated Oct. 27, 1897 (DCSO records Vol 4 Pg 1474)

Could find no trace of old standard ¼ sec. cor.
Set a sandstone, 12x12x10 ins., 8" in the ground, for standard ¼ sec. cor., mkd. S C ¼ on S. face, from which
A Hemlock 24" dia., bears S.25°E., 34 lks, mkd. S C ¼ S BT
A Maple 14" dia., bears S.4°W., 59 lks., mkd. S C ¼ S BT
This cor. is on the northerly slope of spur, 500 ft. below top.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12630-31)

The standard ¼ sec. cor., monumented with a sandstone 12x12x10 ins. firmly set, mkd. SC ¼ on S. face, from which the remains of the original bearing trees:

A Hemlock stump bears S.25°E., 34 lks. dist.
A Maple stub bears S.4°W., 59 lks. dist.

At the corner point

Set an iron post, 3 ft. long, 1" dia., 30" in the ground, with brass cap mkd:

¼ S 5
S C
1955

from which

A Fir 18" dia., bears S.20°E., 48 lks., mkd. ¼ S5 SC BT
A Cedar 7" dia., bears S.28°W., 47 lks., mkd. ¼ S5 SC BT
Deposit the original corner stone alongside the iron post, properly oriented.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2874, surveyed AUG. 2017- (DCSO records Vol. 59 Page 23795 & Plat T23-6 2020-1)

The standard ¼ sec. cot of sec. 5 only, on the N. bdy. of the Tp., monumented with an iron post, 1" dia. firmly set, projecting 6" above ground, with a brass cap (properly) mkd from which a BT mkd. by Gould, Gawron, and Eggen in 1943-57

continued next page

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 240700

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. Section 5 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 30" dia., bears S.17 $\frac{3}{4}$ °E, 31.7 ft., with a healed blaze. (Record, bears S.20°E.)
and a new bearing tree
A cedar, 19" dia., bears S.41 $\frac{1}{4}$ °W, 49.0 ft. mkd. $\frac{1}{4}$ S5 SC BT