

PRIMARY CORNER DESCRIPTION C C for Secs. 32 & 33 only, T22-6

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Special Instructions dated Oct. 27, 1897 and Contract #664 dated May 23, 1896 (DCSO records Vol. 4 Page(s) 1481-82)

Set a sandstone 16x8x8 ins., 11" in the ground, for a closing cor. of secs. 32 and 33 mkd. C C on N. with 2 grooves on W. and 4 grooves on E. faces; from which

A Fir 8" dia., bears N.11½°W., 74 lks. dist., mkd. T22S R6W S32 BT.

A Fir 6" dia., bears N.48½°E., 130 lks. dist., mkd. T22S R6W S33 BT.

This cor. is on a steep NW. slope, 50 ft. above ravine.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12630)

The closing cor. of secs. 32 and 33, T22S R6W, determined at record bearing and distance from the original bearing trees:

A Fir 42" dia., bears N.11½°W., 74 lks. dist., with a healed blaze.

A Fir 48" dia., bears N.48½°E., 130 lks. dist., with a healed blaze.

At the corner point

Set an iron post, 3 ft. long, 2" dia., 30" in the ground, with brass cap mkd:

C C  
T22SR6W  
S32\*S33  
S 5  
T23SR6W  
1955

from which

A Fir 14" dia., bears N.46½°W., 23 lks. dist., mkd. T22S R6W S32 CC BT.

A Fir 12" dia., bears N.63½°E., 35 lks. dist., mkd. T22S R6W S33 CC BT.

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor Under Group No. 2653, Surveyed June/July 2012 - DCSO records Vol. 58 Page(s) 22984

The closing cor. of secs. 32 and 33, on the S. bdy. of the Tp., monumented with an iron post, 2" dia., firmly set, projecting 7" above ground, with brass cap (properly) mkd. from which the remains of an original bearing tree

A sawed, decayed fir stump, 40" dia., bears N.11½°W., 56.3 ft., with no marks visible. (Record, 48.8 ft.)

continued next page

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 271700

PRIMARY CORNER DESCRIPTION C C for Secs. 32 & 33 only, T22-6

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

and remains of bearing trees mkd. by Gould, Gawron, and Eggen  
A fir snag, 11" dia., bears N.63½°E., 23.1 ft., with a  
healed blaze.

A sawed, decayed fir stump, 19" dia., bears N.46½°W., 15.2  
ft., with a healed blaze.

and new bearing trees

A fir, 16" dia., bears N.8°E., 25.8 ft., mkd. T22S R6W S33  
CC BT.

A fir, 7" dia., bears N.64¾°W., 44.3 ft., mkd. T22S R6W  
S32 CC BT.

Corner is located on a NW. slope, 215 ft. S. of a ravine,  
drains N.70°W.