

PRIMARY CORNER DESCRIPTION Sec. Cor. for 16, 17, 20 and 21

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 6 Page(s) 2433)

Set Cedar post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 16, 17, 20 and 21 mkd. T23S S16 on NE.; R6W S21 on SE.; S20 on SW.; and S17 on NW. faces, with 3 notches on S. and 4 notches on E. edges, from which

- A Cedar 12" dia., bears N.14°E., 8 lks. dist. mkd. T23S R6W S16 BT.
- A Fir 8" dia., bears S.20°E., 37 lks. dist. mkd. T23S R6W S21 BT.
- A Fir 24" dia., bears S.33°W., 13 lks. dist. mkd. T23S R6W S20 BT.
- A Fir 18" dia., bears N.70°W., 30 lks. dist. mkd. T23S R6W S17 BT.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12695)

The Sec. cor., determined from two original bearing trees:

- A Fir 26" dia., dead and down, bears S.41°E., 37 lks. dist. mkd. S21 BT. (Record brg. & dist., S.20°E.)
- A Fir 26" dia., bears N.20°W., 30 lks. dit. mkd. T23S R6W (Rec. brg. N.70°W.)

At the corner point
Set an iron post, 3 ft. long, 2" dia., 28" in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd:

T23SR6W
<u>S17</u> <u>S16</u>
S20 S21
1957

from which

- A Fir 25" dia., bears N.66½°E., 17 lks. dist. mkd. T23S R6W S16 BT.
- A Cedar 14" dia., bears S.52°E., 36 lks. dist. mkd. T23S R6W S21 BT.
- A Hemlock 14" dia., bears S.69°W., 70 lks. dist. mkd. T23S R6W S20 BT.
- A Fir 24" dia., bears N.27°W., 32 lks. dist. mkd. T23S R6W S17 BT.

BLM Resurvey - James E Jelley, Wayne L. Rogers, and Lance J. Bishop, Cadastral Surveyors Under Group # 1098 - Surveyed June 1982/Nov. 1983 (DCSO records Vol. 46 Page(s) 17733-34)

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 16, 17, 20 and 21

Alias	Description
Alias	Description
Alias	Description
Alias	Description

The Sec. cor., monumented with an iron post, 2" dia., firmly set, projecting 10" above ground, with 1957 brass cap from which the remaining original bearing tree:
A Fir 28" dia., bears N.20°W., 30 lks. dist., with scribe marks T23S R6W S17 BT visible on bark blaze.
and bearing trees mkd. by Gould, Gawron, and Eggen:
A Fir 32" dia., bears N.66½°E., 17 lks dist., with healed blaze.
A Cedar 24" dia., bears S.52°E., 36 lks. dist. with healed blaze.
A Fir 14" dia., bears N.24¼°W., 32 lks. dist., with scribe marks T23S R6W S17 BT visible on open blaze. (Rec. N.17°W.)
and new bearing trees:
A Yew 12" dia., bears S.42¼°E., 57 lks. dist., mkd. T23S R6W S21 BT.
A Fir 12" dia., bears S.32 3/4°W., 58 lks. dist., mkd. T23S R6W S20 BT.

From this point, a corner established by Wilford N. Haines #239, in 1957, bears N.46°27'E., 0.25 chs. dist., monumented with a "T" shaped iron rod, 3/4" dia., loosely set, projecting 15" above ground.

Fd. OK, August 1990, M 110-53

Fd. & used on BLM corrective & dependent resurvey by Wayne L. Rogers, Cadastral Surveyor & Robert H. Browning, Surveying Technician, under Group #1803 surveyed May/Nov.. 1996 - (DCSO records Vol. 52 Page(s) 19956)

BLM resurvey by Joel R Herzberg, Cadastral Surveyor under Group No. 2778 - surveyed May 2015/July 2016 - (DCSO records Vol. 59 Page(s) 23553

The cor. of secs. 16, 17, 20, & 21, monumented with an iron post, 2" dia., firmly set, projecting 12" above the ground, with brass cap (properly) mkd. from which the remains of an original BT reported by Rogers and Browning in 1996
A fir, 36" dia., bears N.16¼°W., 18.2 ft., with fragmentary scribe marks visible on bark blaze.
and the remaining BTs mkd. by Gould, et. al., in 1943-57 and reported by Rogers and Browning
A fir, 39" dia., bears N.66½°E., 11.2 ft., with a healed blaze.
A fir, 22" dia., bears N.24¼°W., 21.1 ft., with a healed blaze.
continued next page

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 16, 17, 20 and 21

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

and bearing tress mkd. by Jelley, et. al., 1982-83 and reported by Rogers and Browning

A yew, 12" dia., bears S.42¼°E., 38.4 ft., with fragmentary scribe marks visible on partially healed blaze. (Record, 37.6 ft.)

A fir, 20" dia., bears S.32¾°W., 38.3 ft., with the root wad of a fallen tree covering the face of the blaze.

Corner is located on steep SE. facing slope.

Note: The "T" iron erroneously established for the cor. of secs. 16, 17, 20, and 21, by Haines, in 1957, recovered and rejected by Rogers and Browning in 1996, was searched for but not recovered.

NAD 1983 (2011)

Latitude: 43°33'43.06" N. Longitude: 123°25'10.52" W.