

PRIMARY CORNER DESCRIPTION Sec. Cor. for 8, 9, 16 and 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by John A McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol 6 Pg 2435)

Set Yew post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 8, 9, 16 and 17, mkd. T23S S9 on NE.; R6W S16 on SE.; S17 on SW.; and S8 on NW.; faces, with 4 notches on S. and E. edges, from which

- A Fir 6" dia., bears N.21°E., 16 lks. dist. mkd. T23S R6W S9 BT.
- A Fir 7" dia., bears S.33°E., 43 lks. dist. mkd. T23S R6W S16 BT.
- A Fir 10" dia., bears S.43°W. 19 lks. mkd. T23S R6W S17 BT
- A Fir 6" dia., bears N.38°W. 47 lks. mkd. T23S R6W S8 BT.

Survey by Wilford N. Haines and Leo J. Martin - For: Harold Woolley and E.G. Whipple, Yoncalla Lumber Co. - April 1957 - RM 1-17 (and Haines field books, H-226 and H-227)

- Set 1" x 36" Angle iron with brass cap.
BTs - 40" I.Cedar S.32°24'E., 94.6 ft.
28" Fir S.04°38'E., 73.0 ft.
32" Fir N.79°E., 42.9 ft.
44" I.Cedar N.07°15'W., 103.0 ft.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12697)

Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 2" dia., 26" in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd:

T23SR6W
S 8 | S 9
S17 | S16
1957

from which

- A Madrone 10" dia bears N.62°E., 46 lks mkd T23S R6W S9 BT
- A Fir 8" dia., bears S.21°E., 135 lks mkd. T23S R6W S16 BT
- A Fir 13" dia., bears S.17°W., 155 lks mkd T23S R6W S17 BT
- A Madrone 11" dia., bears N.26°W., 78 lks. dist. mkd. T23S R6W S8 BT.

continued next page

PRIMARY CORNER DESCRIPTION Sec. Cor. for 8, 9, 16 and 17

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Ken Hoffine - For: Juniper Properties Limited - July 2010 - M161-9

Found - 1957 BLM brass cap 0.8 ft above ground.
18" madrone stump bears N.24 $\frac{3}{4}$ °W., 51.8 ft (rec N.26°W., 51.48 ft) unreadable tag, no visible marks
20" D.Fir bears S.17 $\frac{3}{4}$ °W., 102.2 ft (record S.17°W., 102.3 ft) unreadable tag, healed face
Haines T-iron bears S.89°48'W., 8.37 ft
Haines BT 51" cedar stump bears N.10 $\frac{3}{4}$ °W., 104.8 ft (rec N.7 15°W., 103.0 ft) visible scribing & tag
Haines BT 42" cedar stump bears S.30 $\frac{1}{4}$ °E., 86.3 ft (record S.32°24'E., 94.6 ft) visible face and tag
Haines BT 32" D.Fir bears S.3 $\frac{1}{2}$ °E., 72.3 ft (record S.4°38'E., 73.0 ft) well healed face and tag
Haines BT 42" D.Fir bears N.77°E., 37.9 ft (record N.79°E., 42.9 ft) no visible marks and tag
Corner lies on west side of main ridge top.

BLM resurvey by Joel R Herzberg, Cadastral Surveyor under Group No. 2778 - surveyed May 2015/July 2016 - (DCSO records Vol. 59 Page(s) 23554-5

The cor. of secs. 8, 9, 16, 17, monumented with an iron post, 2" dia., firmly set, projecting 9" above the ground, with brass cap (properly) mkd. from which the remains of BTs mkd. by Gould, in 1943-57
A fir snag, 9" dia., bears S.21°E., 89.1 ft., with illegible scribe marks visible on decayed partially healed blaze.
A fir, 21" dia., bears S.17°W., 102.3 ft., with a healed blaze.
A madrone stump, 19" dia., bears N.26°W., 51.5 ft., with no marks visible.
and the remains of BTs mkd. by Haines, PLS No. 239, in 1957
A fir, 42" dia., bears N.72 $\frac{1}{2}$ °E., 30.0 ft., with a healed blaze.
A cedar stump, 42" dia., bears S.25 $\frac{3}{4}$ °E., 82.4 ft., with marks R W and other fragmentary scribe marks visible on partially healed blaze.
A fir, 30" dia., bears S.3°W., 71.9 ft., with a healed blaze.
A cedar stump, 53" dia., bears N.15 $\frac{1}{4}$ °W., 106.7 ft., with fragmentary scribe marks visible on partially healed blaze.

Note: the bearing trees mkd. by Haines now reference the cor. reestablished by Gould, et. al.

continued next page

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 8, 9, 16 and 17

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

and a new bearing tree

A fir, 10" dia., bears N.10°W., 27.5 ft., mkd. T23S R6W S8 BT.

From this cor., a point erroneously reestablished for the cor. of secs. 8, 9, 16, and 17, by Haines, in 1957, bears S.89°14'52"W. 8.40 ft., and was not accepted for the cor., and now functions as a reference monument; monumented with a "T" iron, 3/4" dia., firmly set, projecting 10" above ground, with a brass washer mkd. WILFORD N HAINES 239 SURVEY POINT DRAIN ORE.