

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John A McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 6 Pg 2436)

Set Cedar post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor., mkd. ¼ S on W. side, from which
A Fir 8" dia., bears N.22°W., 18 lks. dist. mkd. ¼ S BT
A Cedar 7" dia., bears S.16°E., 38 lks. dist. mkd. ¼ S BT

Survey by Wilford N. Haines and Leo J. Martin - For: Harold Woolley and E.G. Whipple, Yoncalla Lumber Co. - April 1957 - RM 1-17 (and Haines field books, H-226 and H-227)

Set 1" x 36" Angle iron with brass cap.
BTs - 10" Fir S.40°E., 42.0 ft.
6" Fir N.88°W., 12.1 ft.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12699)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 30" long, 2" dia., 28" in the ground, with brass cap mkd:
T23SR6W
¼
S8|S9
1957

from which
A Chinquapin 12" dia., bears S.70°E., 43 lks mkd. ¼ S9 BT.
A Fir 10" dia., bears S.48°W., 89 lks. dist. mkd. ¼ S8 BT.

Wilford N. Haines - June 29, 1962 - C.S. File 51/222-3

Found - GLO brass cap and following trees:
12" Chinquapin S.70°E., 43 lks., is gone.
10" Fir S.84°W., 89 lks., fire and bug killed. (Rec. S.48°W., ((by VL, July 1985)))
New BTs -16" Fir S.4°E., 31.0 ft.
10" Fir N.87°W., 42.7 ft.

BLM resurvey by Joel R Herzberg, Cadastral Surveyor under Group No. 2778 - surveyed May 2015/July 2016 - (DCSO records Vol. 59 Page(s) 23556)

The ¼ sec. cor. of secs. 8 and 9, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap (properly) mkd.
continued next page

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the BTs mkd. by Haines, PLS No. 239, in 1957
A fir, 34" dia., bears S.4°E., 30.6 ft., with a healed blaze.
A fir, 32" dia., bears N.87½°W., 42.9 ft., with a healed blaze.
and a BT mkd. by person(s) unknown
A fir, 17" dia., bears S.47¾°E., 15.3 ft., with a healed blaze and an aluminum nail driven into the left side center.
Note: the BTs mkd. by Haines now reference the cor. reestablished by Gould, et. al., in 1943-57.
From this cor., a point erroneously reestablished for the ¼ sec. cor. of secs. 8 & 9, by Haines, in 1957, bears N.86°18'41"W., 30.90 ft., and was not accepted for the cor. and now functions as a reference monument, monumented with a "T" iron, 3/4" dia., firmly set, projecting 2" above the ground, with a brass washer mkd. WILFORD N HAINES 239 SURVEY POINT DRAIN ORE.

Douglas Co. Surveyors Office - Crew: Stephen J Flause & Jeff Lorsung - 2/26/2020 - C.S. File 67/46-31

Found OK
Fir BT N.87½°W., now 6 ft tall sawn shop.