

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4, 5, 8 and 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 6 Page(s) 2437)

Set Yew post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 4, 5, 8 and 9, mkd. T23S S4 on NE.; R6W S9 on SE.; S8 on SW.; and S5 on NW. faces, with 5 notches on S. and 4 notches on E. edges, from which

- A Fir 12" dia., bears N.13°E., 17 lks. dist. mkd. T23S R6W S4 BT.
- A Fir 18" dia., bears S.20°E., 16 lks. dist. mkd. T23S R6W S9 BT.
- A Cedar 10" dia., bears S.30°W., 50 lks. dist. mkd. T23S R6W S8 BT.
- A Laurel 10" dia., bears N.81°W., 20 lks. dist. mkd. T23S R6W S5 BT.

Wilford N. Haines #239 - For: Whipple Mill - Sept. 1956 - M 3-8 and April 1957 survey RM 1-17 (FB. H-226 and H-227)

Found - A BT, S.20°E., 16 lks.
Ed Williams showed me where he had seen a BT that fit the description of tree, N.13°E., 17 lks.
Set a 36" angle iron with brass cap inscribed "Survey point Wilford N. Haines #239"
Scribed new trees:
14" I.Cedar N.53°W., 12.7 ft.
48" Fir N.44°E., 41.0 ft.
14" I.Cedar S.44°W., 36.7 ft.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12699-700)

The sec. cor., determined at record bearing and distance from an original bearing tree:

A Fir 24" dia., bears S.20°E., 16 lks. dist. mkd. BT.
At the corner point
Set an iron post, 30" long, 2" dia., 12" in the ground, and in a mound of stone, 8 ft. base, to top, with brass cap mkd:
T23SR6W
S5|S4
S8|S9
1957

from which
A Cedar 16" dia., bears N.33°E., 53 lks. dist. mkd. T23S R6W S4 BT.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4, 5, 8 and 9

Alias	Description
Alias	Description
Alias	Description
Alias	Description

- A Cedar 12" dia., bears S.12°E., 88 lks. dist. mkd. T23S R6W S9 BT.
- A Cedar 24" dia., bears S.42°W., 68 lks. dist. mkd. T23S R6W S8 BT.
- A Cedar 28" dia., bears N.32°W., 55 lks. dist. mkd. T23S R6W S5 BT.

Fd. OK, Feb. 1993, K.Hoffine, C.S. File 63/149-6

BLM resurvey by Joel R Herzberg, Cadastral Surveyor under Group No. 2778 - surveyed May 2015/July 2016 - (DCSO records Vol. 59 Page(s) 23556-7

The cor. of secs. 4, 5, 8, & 9, monumented with an iron post, 2" dia., firmly set, projecting 16" above the ground, in a collar of stone, with brass cap (properly) mkd. from which the remains of an original BT reported by Gould, et. al., in 1943-57

A decayed fir stump, 24" dia., bears S.20°E., 10.6 ft., with axe marks visible on opened blaze. and remains of the BTs mkd. by Gould, et. al.

A cedar, 24" dia., bears N.33°E., 35.0 ft., with a healed blaze.

A decayed cedar stump with tin cap, 17" dia., bears S.13½°E., 58.1 ft., with a healed blaze. (Record, S.12°E.)

A decayed cedar stump, 19" dia., bears S.42°W., 44.9 ft., with scribe marks T23S R6W S8 BT visible on partially healed blaze.

A cedar, 33" dia., bears N.32°W., 36.3 ft., with scribe marks S R6W S5 visible on partially healed blaze. and remains of the bearing trees mkd. by Haines, in 1957

A decayed fir stump, 54" dia., bears N.45¾°E., 41.2 ft., with no marks visible.

A decayed cedar stump, 21" dia., bears S.45¾°W., 36.3 ft., with scribe marks SR6WB visible on partially healed blaze.

A cedar, 23" dia., bears N.50¼°W., 11.4 ft., with fragmentary scribe marks visible on partially healed blaze.

The point established for the cor. of secs. 4, 5, 8, & 9, by Haines, in 1957, monumented with a "T" iron, ¾" dia., firmly set, projecting 16" above ground, with a brass washer mkd. WILFORD N HAINES 239 SURVEY POINT DRAIN ORE is alongside the cor. and was not utilized for control in the course of this survey.