TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 300640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 5

Alias Description
Alias Description
Alias Description
Alias Description

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 6 Page(s) 2439)

Set Cedar post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor., mkd. ¼ S on W. face, from which
A Fir 8" dia., bears S.15°E., 37 lks. dist. mkd. ¼ S BT
A Fir 4" dia., bears S.32°W., 38 lks. dist. mkd. ¼ S BT

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12701)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 30" long, 2" dia., 28" in the ground, with brass cap mkd:

T23SR6W
¼
S5 S4
1957

from which
A Fir 13" dia., bears S.10°E., 49 lks. dist. mkd. ¼ S4 BT
A Cedar 20" dia., bears S.75°W., 50 lks. dist. mkd. ¼ S5 BT.

Fd. OK - Ken Hoffine - Dec. 1995 - C.S. 65/2-1