

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 33; & S. 4, T24-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 6 Page(s) 2389)</p> <p>-----</p> <p>Set ¼ sec. post, from which A Chinquapin 12" dia., bears S.59°E., 69 lks. A Fir 14" dia., bears N.11°W., 52 lks.</p>
<p>GLO survey by William R. Whipple, Deputy Surveyor, under Contract #577, dated July 18, 1891 (DCSO records Vol. 8 Page(s) 3181)</p> <p>-----</p> <p>Set a chestnut post, 4 ft. long, 4" sq., 24" in the ground for ¼ sec. cor., mkd. ¼ S on N. face, from which A Fir 5" dia., bears S.9°15'E., 69½ lks. dist. mkd. ¼ S BT A Fir 29" dia., bears N.50°45'W., 50 lks. dist., mkd. ¼ S BT.</p>
<p>BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12646)</p> <p>-----</p> <p>The ¼ sec. cor., determined at record bearing and distance from the remains of an original bearing tree: A Fir 37" dia., bears N.50 ¾°W., 50 lks. dist., mkd. BT At the corner point Set an iron post, 3 ft. long, 2" dia., 24" in the ground, with brass cap mkd: T23SR6W ¼ $\frac{S \ 33}{S \ 4}$ T24S 1957</p> <p>from which A Fir 6" dia., bears N.25¼°E., 61 lks. dist., mkd. ¼ S33 BT A Fir 16" dia., bears S.76½°E., 91 lks. dist., mkd. ¼ S4 BT</p>
<p>Fd. OK, May 6, 1982, H. Johnstone, M 92-17</p>
<p>Fd. and Used in BLM Corrective Dependent Resurvey by Wayne L. Rogers; Boyd W. Peterson; Philip G. Griffin; Dale T. Bedell; Cadastral Surveyors; and Robert H. Browning, Surveying Technician - under Group #'s 1266, 1637 and 1688, - surveyed June 9, 1986/August 22, 1995 - (DCSO records Vol. 51 Page(s) 19449)</p>