

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664 dated May 23, 1896 and under Special Instructions dated Oct. 27, 1897 (DCSO records Vol. 4 Page(s) 1479-80)

Intersect corner 8.36 chs. N.89°48'W. of the standard cor. of secs. 3 & 4
At point of intersection
Set a sandstone, 12x10x8 ins. 8" in the ground for a closing cor. of secs. 33 and 34, mkd. C C on N. with 3 grooves on E. and W. faces, from which
 A Fir 40" dia., bears N.55°E., 21 lks. dist., mkd. T22S R6W S34 BT.
 A Fir 36" dia., bears N.62°W., 100 lks. dist., mkd. T22S R6W S33 BT.
This cor. is on the steep S. slope of ridge, 200 ft. below top.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12628)

The closing cor. of secs. 33 and 34, T22S R6W, determined at record distance from the remains of the original bearing trees:
 A Fir dead and down, 50" dia., bears N.83°W., 100 lks. dist., mkd. T22S R6W S33 CC BT. (Rec. brg. N.62°W)
 A stump hole bears N.55°E., 21 lks. dist.
At the corner point
Set an iron post, 3 ft. long, 2" dia., 24" in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd:
 C C
 T22SR6W
 S33|S34
 S 4
 T23SR6W
 1955
from which
 A Fir 7" dia., bears N.33°E., 25 lks. dist., mkd. T22S R6W S34 CC BT.
 A Fir 6" dia., bears N.67°W., 36 lks. dist., mkd. T22S R6W S33 CC BT.

Douglas Co. Surveyors Office - Randall Smith, Stephen Flause, crew - Feb. 18, 1992 - C.S. File 64/24-6

Found - 2" dia. GLO brass cap on a 1½" O.D. Iron pipe flush with ground. (1955) (Cont. Next Page)

PRIMARY CORNER DESCRIPTION CC for Secs. 33 & 34 only, T22-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

6" now 18" dia., D.Fir with a fully healed single blaze, bears N.67°W., 23.8 ft. (agrees w/rec)
7" now 19" dia. D.Fir with a fully healed single blaze, bears N.33°E., 16.5 ft. (agrees w/rec)
No evidence remaining of original NE BT.
36" now down and rotting D.Fir of indeterminable size, no blazes or scribing visible, possible root hole, bears N.83°W., 66.0 ft. (agrees w/BLM rec) Orig. BT.
New BTs -15" dia. D.Fir double blazed and scribed "T22S R6W CC S33 CS BT" bears N.10°W., 15.8 ft.
11" dia. D.Fir double blazed and scribed "T22S R6W CC S34 CS BT" bears N.82°E., 30.3 ft.
Corner is approx. 30 ft. East of a West and North running cut line corner.

Fd. B.C., J. Branch, June 1992, M 115-23
Fd. OK - K. Hoffine, Dec. 1995, C.S. 65/2-1

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor Under Group No. 2653, Surveyed June/July 2012 - DCSO records Vol. 58 Page(s) 22981

The closing cor. of secs. 33 and 34, on the S. bdy. of the Tp., perpetuated by the Douglas County Surveyor's Office in 1992, monumented with an iron post, 2" dia., firmly set, projecting 12" above ground, in a collar of stone, with brass cap (properly) mkd.
from which the remains of an original bearing tree
A roothole bears N.78°W., 66.0 ft., downhill of which is a fallen, decayed fir snag, 30" dia., with no marks visible. (Record, N.83°W.)
and bearing trees mkd. by Gould, Gawron, and Eggen
A fir, 21" dia., bears N.33°E., 16.5 ft., with a healed blaze.
A fir, 23" dia., bears N.67°W., 23.8 ft., with a healed blaze.
and BTs mkd. by the Douglas County Surveyor's Office
A fir, 10" dia., bears N.83¼°E., 29.5 ft., with a healed double blaze.
A fir, 21" dia., bears N.10°W., 15.1 ft., with a healed double blaze.
Corner is located on a SW. slope, 140 ft. E. of a ravine, drains S.40°E.

NAD 1983 (CORS 96)
Latitude: 43°36'22.47"N Longitude: 123°24'29.65"W

continued next page

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 372700

PRIMARY CORNER DESCRIPTION C C for Secs. 33 & 34 only, T22-6

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2875, surveyed Aug. 2017/Feb. 2019- (DCSO records Vol. 59 Page 23642-3)

The closing cor. of secs. 33 and 34, on the S. bdy. of the Tp., monumented with an iron post, 2" dia., firmly set, projecting 6" above ground, with a brass cap (properly) mkd. from which the bearing trees mkd. by Gould, Gawron, and Eggen in 1943-57

A fir, 21" dia., bears N.33°E., 16.5 ft., with a healed blaze.

A fir, 23" dia., bears N.67°W., 23.8 ft., with a healed blaze.

and the remains of the bearing trees mkd. by Douglas County Surveyors Office in 1992

A broken fir snag, 10" dia., bears N.83¼°E., 29.5 ft., with a healed blaze.

A fir, 22" dia., bears N.10°W., 15.1 ft., with a healed blaze.

The geographic position in NAD 1983 (2011)

Latitude: 43°36'22.47"N Longitude: 123°24'29.65" W.